



Recommended Panel Cut-Out

Material:

- Waterproof Rate: IP67
- LED Holder: Brass, Nickel plating
- LED: ø3MM, Yellow
- Forward Voltage: Yellow Typ. 2.0V/Max.2.4V
- Forward Current: Yellow Max. 30mA
- Luminous Intensity: Yellow Min.770/ Typ.1,600(Mcd)
- Operating Voltage: 4V DC
- Reverse Voltage: 5V DC
- Gasket: EPDM, Black
- Screw Nut: Brass, Nickel plating
- Operating Temperature: -40°C~+80°C
- For Panel Thickness 6.5MM Max.

QC Quality Control: Important Dimension to check
Unit: MM±0.25MM

⊕ = Assmann logo



ITEM NO.	A-LED8-1YAAS-MR7-1-R
TITLE	Waterproof LED - Yellow color, M8 size connector, ø3MM, Metal housing, Solder pins, IP67 unmated

ASSMANN
Electronics, Inc.

1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283
Toll Free: 1-877-277-6266 • Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
©Copyright 2010 by Assmann Electronic Components
All International Rights Reserved