

4



3

2



1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS		
P	LTR	DESCRIPTION	DATE	BY
AD	00			
B1		REVISED PER ECO-11-005027	11MAR11	RK HMR



SIDE VIEW
(SEE NOTE 3)



SPECIFICATIONS:

- LAMP DISSIPATION: 1.2W MAX.
- INSULATION RESISTANCE: 100 MEGOHMS MIN.
- DIELECTRIC STRENGTH: 2000 VAC.
- OPERATING TEMPERATURE: -20°C TO +50°C
(-4°F TO +122°F).

NOTES:

- LAMP IS T 3/4 MIDGET FLANGE BASE TYPE (LAMP NOT SUPPLIED).
- 164 IS NON-DILTIGHT SERIES, 165 IS DILTIGHT SERIES.
- VIEWS INCLUDE PLASTIC SHROUDS FOR AVAILABLE LENS SETS, (NOT SUPPLIED).

- THE PLATINGS CONTAINED IN THIS PART SHALL CONTAIN NO LEAD.
- PRELIMINARY PART, NOT RELEASED FOR PRODUCTION.

1571542-4	165TZ	
1571542-3	164TZ	
1571542-2	164SZ	
1571542-1	164EZ	
5-1437569-9	165TZ	
5-1437569-3	165SZ	
4-1437569-6	165EZ	
4-1437569-1	164TZ	
3-1437569-2	164SZ	
1437569-8	164EZ	
PART No.	MODEL NUMBER	

REF AUGAT 81091

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPROVED:		TE Connectivity	
INCHES	0 PLC ± .005	1 PLC ± .005	2 PLC ± .010	3 PLC ± .010	4 PLC ± .010	5 PLC ± .010	TE Connectivity
	ANGLES	± .010	± .010	± .010	± .010	± .010	PILOT LIGHT 164/165 Z
MATERIAL	FINISH			APPLICATION SPEC	PRODUCT SPEC	SIZE	CAGE CODE
						A2	00779
				WEIGHT		DRAWING NO	2-1437569-4
						SCALE	NTS
						SHEET	1 of 1
						REV	B1