



SCHMATIC

- NOTE:
1. THIS PRODUCT REQUIRES EXTERNAL RESISTOR. (NO RESISTOR IN THIS PACKAGE).
  2. LIGHT COLOR: RED & GREEN. RED WIRE TO (+) RED LIGHT ON. GREEN WIRE TO (+) GREEN LIGHT ON.
  3. WIRE LEADS: 24 AWG, 7/32 STRANDED. PRE-BONDED, TYPE C. MIL-W-168780 UL STYLE 1569; CSA TR-64. INSULATION PVC WITH VW-1 FLAME TEST APPROVED DESIGNATION.

BI-COLOR LED						
OPERATING CHARACTERISTICS AT $T_A = 25^\circ C$						
PARAMETER	COLOR	MIN	TYP	MAX	UNITS	TEST COND.
FORWARD VOLTAGE	RED	1.8	2.4		V	$I_F = 20 \text{ mA}$
	GREEN	2.1	2.8			
PEAK WAVELENGTH	RED	660			nm	MEASURED AT PEAK
	GREEN	565				
LUMINOUS INTENSITY	RED	14	60		mcd	$I_F = 20 \text{ mA}$
	GREEN	9	20			
CONTINUOUS FORWARD CURRENT	RED		40		mA	
	GREEN		30			
REVERSE CURRENT	RED			100	mA	$V_R = 5 \text{ v}$
	GREEN					
VIEWING ANGLE ( $2\theta_{1/2}$ )	RED		80		deg.	
	GREEN					
CAPACITANCE	RED		30		pF	$V_F = 0; f = 1 \text{ MHz}$
	GREEN		35			
ABSOLUTE MAXIMUM RATINGS AT $25^\circ C$ .		RED	GREEN	UNITS		
POWER DISSIPATION		100	100	mW		
DERATE LINEARY FROM $25^\circ$		.5	.4	mA/ $^\circ C$		
PEAK FORWARD CURRENT		200	120	mA		
REVERSE VOLTAGE		4	5	V		
OPERATING TEMPERATURE RANGE		-55 TO +100		$^\circ C$		
STORAGE TEMPERATURE		-55 TO +100		$^\circ C$		

A	NEW RELEASE	L.R. 7.8.2-18-97
LTR	ECN NO.	REVISIONS
THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT. REPRODUCTION OF THIS DRAWING OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE PRIOR WRITTEN CONSENT OF DIALIGHT.		
SCALE: 1:1	CUSTOMER DRAWING NO.	DWG. REV.
TOLERANCES: UNLESS OTHERWISE SPECIFIED	C-16193 A	
ALL DIM'S IN: INCHES	TITLE	
FRACTIONS: $\pm 1/64$	RED/GREEN BI-COLOR VDC LED	
DECIMALS(.XX) $\pm .020$	PANEL MOUNT 2 LEADS INDICATOR	
DECIMALS(.XXX) $\pm .015$	PART NUMBER	
ANGLES $\pm 3^\circ$	557-0001-806	
FINISH:	Dialight	
FSCM 83330	1913 Atlantic Ave. Manasquan, NJ 08736	