Optolite Products

General Purpose



99-33180 Type **Incandescent Subminiature** Size T-1



Material and Finishes

Mounting tube, black glass filled nylon per MIL-M-19887. Mounting nut aluminum, black anodized per MIL-A-8625A. Lockwasher, stainless steeel or steel, nickel plate. Brass terminals, tin plated per MIL-T-10727A.

Cap Assembly


Lens, high impact-resistant plastic per L-P-349.

T-1 sub-midget flange base.


Mounting

Assembly mounts from front of panel. All mounting hardware supplied. Recommended mounting hole .328 in. +.015 in. -.000

Approx. .12 oz. less lamp







11-33480 Type **Originally designed to** meet MS 25256 **Base LH 73/1 Incandescent Miniature** Size T-1 ¾



14-30080 Type

Size T-1 ¾

Incandescent Miniature

Material and Finishes

Mounting tube and nuts, aluminum, black anodized per MIL-A-8625A. Lockwasher, stainless steel or steel, nickel plate. Brass terminals, tin plated per MIL-T-10727A.


Cap Assembly

Lens, high impact-resistant plastic per L-P-349.

Lamp T-1 ¾ midget flange base.


MountingAssembly mounts from front of panel. All mounting hardware supplied.

Approximately .2 oz. less lamp.









Materials and Finishes

Mounting tube and nuts, aluminum, black anodized per MIL-A-8625A. Lockwasher, stainless steel or steel, nickel plate. Brass terminals, tin plated per MIL-T-10727A.


Cap Assembly

Lens, high impact-resistant plastic per L-P-349. Lens holders, aluminum, black anodized.

Lamp

T-1 ¾ midget flange base.

MountingAssembly mounts from rear of panel. All mounting hardware supplied. Recommended mounting hole .500 in. +/- .015 in. dia.





Sunlight Cap 91050M-()



91050-5()



Sunlight Cap 10852M-()LB



10852-()L









Approx. .27 oz. less lamp. **Schematic**





Downloaded from Elcodis.com electronic components distributor



General Purpose


Optolite Products

BASE ASSEMBLY 13-30080\$

%-24 UNEF

Identification

CAP STYLES



Materials and Finishes

Mounting tube and nuts, aluminum, black anodized per MIL-A-8625A. Lockwasher, stainless steel or steel, nickel plate. Brass terminals, tin plated per MIL-T-10727A.

Cap Assembly

Lens, high impact-resistant plastic (nylon). Standard colors are semidiffusing.

Lamp

T-3 ¾ miniature bayonet base.

Mounting


Assembly mounts from rear of panel. All mounting hardware supplied. Recommended mounting hole .640 in. +/- .015 in. dia.

13-VM 305 Type **Incandescent General Purpose** Size T-3 ¾



BASE ASSEMBLY 14-35180

CAP STYLES



Materials and Finishes

Mounting tube and nuts, aluminum, black anodized per MIL-A-8625A. Lockwasher, stainless steel or steel, nickel plate. Brass terminals, tin plated per MIL-T-10727A.

Cap Assembly

Lens, high impact-resistant plastic per L-P-349.

Lamp

T-1 ¾ midget flange base.


MountingAssembly mounts from rear of panel. All mounting hardware supplied. Recommended mounting hole .500 in. +/- .015 in. dia.

Weight Approx. .2 oz. less lamp

14-35180 Type **Incandescent Miniature** Size T-1 ¾




BASE ASSEMBLY



SCHEMATIC

CAP STYLES



Materials and Finishes

Mounting tube and nuts, aluminum, black anodized per MIL-A-8625A. Lockwasher, stainless steel or steel, nickel plate. Terminals 6-32 screws, nickel plate. Round front mounting nut, bright nickel plate.

Lamp

T-1 ¾ midget flange base. Mounting

Assembly mounts from rear of panel. All mounting hardware supplied. Recommended mounting hole .500 in. +/- .015 in. dia.

14-32280 Type **Incandescent Miniature** Size T-1 34




Optolite Products

General Purpose



59-52480 Type **Incandescent Miniature Size T-1 3/4**



Materials and Finishes

Mounting tube and nuts, aluminum, black anodized per MIL-A-8625A. Lockwasher, stainless steel or steel, nickel plate. Brass terminals, tin plated per MIL-T-10727A.

Cap Assembly Lens, high impact-resistant plastic


per L-P-349. **Lamp**

T-1¾ midget flange base. Mounting

Approx. .2 oz. less lamp.

Assembly mounts from rear of panel. All mounting hardware Weight

SCHEMATIC



33-30881 Type **Neon Miniature** Size T-2



Materials and Finishes

Mounting tube gold anodized, rear mtg. nut aluminum, black anodized per MIL-A-8625A. Lockwasher, stainless steel or steel, nickel plate. Terminals, brass, tin plated per MIL-T-10727A. Round front mtg. nut, bright nickel plate Cap Assembly

Lens, high impact-resistant plastic per L-P-349. Standard colors are transparent.

A1G (std.) or A1H (high brightness) T-2 neon is furnished with each assembly.


Mounting

Assembly mounts from rear of panel. All mounting hardware supplied. Recommended mounting hole .500 in. +/- .015 in. dia.


Approx. .35 oz. less lamp.

BASE ASSEMBLY

33-30881 (68KΩ Internal Resistor)



CAP STYLES



SCHEMATIC

