

DELPHI SERIES



FEATURES

- ♦ High efficiency: 90.5% @ 3.3V/20A
- ♦ Size: 33.0x22.9x9.5mm (1.3"x0.90"x0.37")
- ♦ Input UVLO and OVP
- ♦ Industry standard footprint and pinout
- ♦ Fixed frequency operation
- ♦ SMD and Through-hole versions
- ♦ OTP and output OCP, OVP (default is auto-restart)
- ♦ Output voltage trim: -20%, +10%
- ♦ Monotonic startup into normal and pre-biased loads
- ♦ 2250V isolation and basic insulation
- ♦ No minimum load required
- ♦ No negative current during power or enable on/off
- ♦ ISO 9001, TL 9000, ISO 14001, QS 9000, OHSAS 18001 certified manufacturing facility
- ♦ UL/cUL 60950 (US & Canada) recognized, and TUV (EN60950) certified
- ♦ CE mark meets 73/23/EEC and 93/68/EEC directive

Delphi Series V48SR, 1/16th Brick 66W DC/DC Power Modules: 48V in, 1.2V~15V, 25A out

The Delphi Series V48SR, 1/16th Brick, 48V input, single output, isolated DC/DC converter, is the latest offering from a world leader in power systems technology and manufacturing — Delta Electronics, Inc. This product family provides up to 66 watts of power or 25A of output current (1.8V and below) in a new 1/16th brick form factor (1.3"x0.90") and pinout. With creative design technology and optimization of component placement, these converters possess outstanding electrical and thermal performance, as well as extremely high reliability under highly stressful operating conditions. Typical efficiency of the 3.3V/20A module is greater than 90.5%. All modules are protected from abnormal input/output voltage, current, and temperature conditions. For lower power needs, but in a similar small form factor, please check out Delta S48SP (36W or 10A) and S48SE (17W or 5A) series standard DC/DC modules.

OPTIONS

- ♦ SMD module available
- ♦ Positive remote On/Off
- ♦ OTP and output OVP, OCP mode (Auto-restart or latch)

APPLICATIONS

- ♦ Optical Transport
- ♦ Data Networking
- ♦ Communications
- ♦ Servers

DATABRIEF
DB_V48SR_02022007


Delta Electronics, Inc.



SPECIFICATIONS

GENERAL SPECIFICATIONS			OUTPUT SPECIFICATIONS		
Input Voltage		36~75V	Voltage Accuracy	Typical	± 1.5%
Switching Frequency	Typical (3.3V)	415KHz	Line Regulation	Typical	± 0.1%
Isolation Voltage	In/Out	2250V	Load Regulation	Typical	± 0.1%
Isolation Capacitance	Typical	1nF	Ripple & Noise	Typical	50 mV
Isolation Resistance	Minimum	10M ohm	Current Limits	Typical	120%
MTBF	Bellcore (3.3V)	2.4m hours	Over Voltage	Typical	120%
OTP	Typical	135°C	Voltage Trim		+10%, -20%
Size	33.0x22.9x9.5mm	1.30"x0.90"x0.37"			

PART NUMBERING SYSTEM



V	48	S	R	1R8	25	N	R	F	A
Product Type	Input Voltage	Number of Outputs	Product Series	Output Voltage	Output Current	ON/OFF Logic	Pin Length/Type		Option Code
V - 1/16th brick	48-36V~75V	S - Single	R - regular	1R2 - 1.2V 1R5 - 1.5V 1R8 - 1.8V 2R5 - 2.5V 3R3 - 3.3V 050 - 5.0V 120 - 12V 150 - 15V	04 - 4.4A 05 - 5.5A 13 - 13A 20 - 20A 25 - 25A	N - Negative P - Positive	R - 0.170" N - 0.145" K - 0.110" M - SMD	F - RoHS 6/6 (Lead Free)	A - standard functions

MODEL LIST

MODEL NAME	INPUT	OUTPUT	EFF @ 100% LOAD
V48SR1R225NRFA	36V~75V	1.2A	84.0%
V48SR1R525NRFA	36V~75V	1.4A	85.0%
V48SR1R825NRFA	36V~75V	1.6A	87.0%
V48SR2R520NRFA	36V~75V	1.8A	89.0%
V48SR3R320NRFA	36V~75V	2.4A	90.5%
V48SR05013NRFA	36V~75V	2.3A	91.0%
V48SR12005NRFA	36V~75V	2.3A	91.0%
V48SR15004NRFA	36V~75V	2.3A	91.0%



MECHANICAL DRAWING

Surface-mount module



SIDE VIEW

Through-hole module



SIDE VIEW

NOTES:
DIMENSIONS ARE IN MILLIMETERS AND (INCHES)
TOLERANCES: X.Xmm±0.5mm(X.XX in.±0.02 in.)
X.XXmm±0.25mm(X.XXX in.±0.010 in.)

CONTACT: www.delta.com.tw/dcdc

USA:

Telephone:
East Coast: (888) 335 8201
West Coast: (888) 335 8208
Fax: (978) 656 3964
Email: DCDC@delta-corp.com

Europe:

Telephone: +41 31 998 53 11
Fax: +41 31 998 53 53
Email: DCDC@delta-es.tw

Asia & the rest of world:

Telephone: +886 3 4526107 x6220
Fax: +886 3 4513485
Email: DCDC@delta.com.tw

WARRANTY

Delta offers a two (2) year limited warranty. Complete warranty information is listed on our web site or is available upon request from Delta. Information furnished by Delta is believed to be accurate and reliable. However, no responsibility is assumed by Delta for its use, nor for any infringements of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Delta. Delta reserves the right to revise these specifications at any time, without notice.