

Single Output, High Reliability

- ◆ Universal Input (85 - 265VAC)
- ◆ Input transient protected
- ◆ 2 year warranty
- ◆ High quality design
- ◆ Peak Power capability

RoHS

Key Market Segments & Applications

Factory Automation	Process Control, NC-Machining, Automotive, Packaging Equipment, Materials Handling, Chemical Processing, Robots
Test & Measurement	Burn-in & Test, Automated Test, Instrumentation, Measurement, Detection
Light Industrial	Gaming, Vending, Printers

Features and Benefits

Feature	Benefit
◆ Input Transient Protected	◆ Withstands harsh environments
◆ 2 Year Warranty	◆ Lower Cost of Ownership
◆ Peak Power capability	◆ Can drive high current start up devices

Specifications

MODELS		ZWS5 ZWS10	ZWS15 ZWS30	ZWS50
ITEMS				
AC Input Voltage range	-	85-265VAC (47-440Hz)		
DC Input Voltage range	-	110 - 330VDC		
Inrush Current (100/200VAC) (1)	A	15 / 30		
Temperature Coefficient	-	<0.02%/°C		
Overcurrent Protection (2)	-	~125%		
Overvoltage Protection	V	~140% diode clamp		~115 - 130%, manual reset
Hold Up Time (Typ) @ 100VAC	ms	17		
Remote Sense	-	None		
Operating Temperature	-	(open frame) -10°C~+60°C, derate linearly to 70% load from 50°C~60°C		
Operating Temperature	-	(with cover) Additional derating applies, please consult Installation Manual		
Storage Temperature	-	-30 to +85°C		
Humidity (non condensing)	-	10 - 95% RH		
Cooling	-	Convection		
Withstand Voltage	-	Input to Ground 2kVAC (20mA), Input to Output 3kVAC (20mA), Output to Ground 500VAC (100mA) for 1 min.		
Isolation Resistance	-	>100M at 25C & 70%RH, Output to Ground 500VDC		
Vibration (non operating)	-	10 - 55Hz (1 minute sweep), 19.6m/s ² constant X, Y, Z 1 hour		
Shock	-	< 196.1 m/s ²		
Safety Agency Approvals	-	UL60950-1, CSA60950-1, EN60950-1, CE Mark		
Conducted & Radiated	EM	EN55022-B, FCC Class B, VCCI-B		
Recommended EMI Filter	-	MAW12R5-22	MAW1201-22 MAW1202-22	MAW1202-22
Weight (Typ)	g	120/120	140/270	370
Size (WxHxD)	mm	See Outline Drawings		
Warranty	-	2 years		

Notes:

(1) 25C ambient (cold start)

(2) Avoid prolonged operation in overload

Output Ratings

Model	Voltage	Adjust Range	Max Curr. A	Peak Curr. A	Load Reg mV	Line Reg mV	Ripple Noise mV	Eff. %
ZWS5-3	3.3V	2.97-3.63	1	1.2	40	20	120	62
ZWS10-3	3.3V	2.97-3.63	2	2.4	40	20	120	62
ZWS15-3	3.3V	2.97-3.63	3	3.6	40	20	120	63
ZWS30-3	3.3V	2.97-3.63	6	7.2	40	20	120	70
ZWS50-3	3.3V	2.97-3.63	10	12	40	20	120	73
ZWS5-5	5V	4.5-5.5	1	1.2	40	20	120	67
ZWS10-5	5V	4.5-5.5	2	2.4	40	20	120	70
ZWS15-5	5V	4.5-5.5	3	3.6	40	20	120	71
ZWS30-5	5V	4.5-5.5	6	7.2	40	20	120	75
ZWS50-5	5V	4.5-5.5	10	12	40	20	120	77
ZWS5-12	12V	10.8-13.2	0.42	0.51	96	48	150	68
ZWS10-12	12V	10.8-13.2	0.85	1.02	96	48	150	70
ZWS15-12	12V	10.8-13.2	1.25	1.5	96	48	150	71
ZWS30-12	12V	10.8-13.2	2.5	3	96	48	150	77
ZWS50-12	12V	10.8-13.2	4.3	5.16	96	48	150	80
ZWS5-15	15V	13.5-16.5	0.34	0.41	120	60	150	68
ZWS10-15	15V	13.5-16.5	0.7	0.84	120	60	150	71
ZWS15-15	15V	13.5-16.5	1	1.2	120	60	150	71
ZWS30-15	15V	13.5-16.5	2	2.4	120	60	150	77
ZWS50-15	15V	13.5-16.5	3.5	4.2	120	60	150	81
ZWS5-24	24V	21.6-26.4	0.22	0.27	150	96	200	70
ZWS10-24	24V	21.6-26.4	0.45	0.54	150	96	200	71
ZWS15-24	24V	21.6-26.4	0.65	0.78	150	96	200	71
ZWS30-24	24V	21.6-26.4	1.3	1.56	150	96	200	78
ZWS50-24	24V	21.6-26.4	2.1	2.52	150	96	200	82
ZWS30-36	36V	32.4-39.6	0.9	1.08	240	144	300	78
ZWS50-36	36V	32.4-39.6	1.4	1.68	240	144	300	82
ZWS30-48	48V	43.2-52.8	0.7	0.84	300	192	400	78
ZWS50-48	48V	43.2-52.8	1.1	1.32	300	192	400	82


Note for Peak Current: For 10s maximum, 35% duty cycle, average power not to exceed maximum ratings.

Options

Suffix	Description
-	Molex Terminals
/A	Cover option
/J	JST Connectors*
/JA	JST Connectors & Cover

Note: * Recommended for new designs

ZWS Outline Drawing



DIMENSIONS:

MODEL	A	B	C	D	E	F	G	H	J	K	L
ZWS5	3.86	1.77	3.880	1.500	-	-	.14	.83	1.05	.54	-
	(98.0)	(44.9)	(90.9)	(38.1)	-	-	(3.5)	(21.0)	(26.6)	(13.7)	-
ZWS10	4.14	1.97	3.880	1.690	-	-	.14	.83	.99	.67	-
	(105.1)	(50.0)	(98.0)	(42.9)	-	-	(3.5)	(21.0)	(25.1)	(18.4)	-
ZWS15	4.93	1.97	4.650	1.690	-	-	.14	.83	1.04	.57	-
	(125.2)	(50.0)	(118.1)	(42.9)	-	-	(3.5)	(21.0)	(25.0)	(14.4)	-
ZWS30	5.24	2.17	4.850	1.770	-	-	.20	1.02	.20	1.16	-
	(133.0)	(55.1)	(123.1)	(45.0)	-	-	(5.0)	(25.9)	(31.0)	(40.2)	-
ZWS50	7.68	2.17	7.290	1.770	-	-	.20	1.02	1.32	.72	-
	(195.0)	(55.1)	(185.1)	(45.0)	-	-	(5.0)	(25.9)	(33.5)	(18.2)	-

Other Lambda Industrial Products

ZWS-AF	50W to 150W Active PFC
ZWD/ZWQ	100W to 440W Single & multiple output
SC	30W to 120W Single, dual, & triple output
HWS	15W to 1800W Single output enclosed

For Additional Information, please visit
us.tdk-lambda.com/lp/products/zws-series.htm