



**CP SNT 24W 24V 1A**

Weidmüller Interface GmbH & Co. KG  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-2083  
 www.weidmueller.com

**Technical data**

**Dimensions (1)**

Length	62.5 mm	Width	52 mm
Height	90.5 mm		

**temperature**

Ambient temperature (operational)	Storage temperature	-40 °C...+85 °C
-----------------------------------	---------------------	-----------------

**Input**

Conductor connection system	Screw connection	DC input voltage range	120...300 V DC
Input current	460 mA @ 115 V AC; 250 mA @ 230 V AC	Input current at 115 Vac	460 mA RMS ± 20%
Input current at 125 Vdc	235 mA ± 20%	Input current at 250 Vdc	120 mA ± 20%
Input frequency	50/ 60 Hz	Input fuse	2 A time-lag fuse (internal)
Input voltage (voltage mode input)	85...265 V AC, 120...300 V DC	Input voltage range AC	85...265 V AC
Surge protection	Varistor	making current limit	Thermistor

**output**

Conductor connection system	Screw connection	Control at 10...100% load	0.5 %
Control at input voltage	0.2 %	Mains failure bridge-over time	35 ms @ 115 V AC / 160 ms @ 230 V AC
Mains failure bridge-over time for 115 V AC	35 ms	Mains failure bridge-over time for 230 V AC	160 ms
Max. capacitance at output	8000 µF	Max. residual ripple	< 2 %
Output current	1 A	Output power, max.	24 W
Output voltage	24 V	Output voltage type	DC
Overload protection	Surge current / thermal cut-out	Surge protection	Varistor
rated output voltage	24 V DC ± 1 %		

**General data**

Ambient temperature (operational)		DIN Rail compatibility	TS 35
Degree of efficiency at max. load	78 %	EMC standards	EN 61000-6 /-2, -3
Mounting position, installation notice	horizontally on terminal rail TS 35	Standards	EN 50178 EN 60950 IEC950
Ambient temperature (operational)	-20 °C...+50 °C		

**Insulation coordination**

electrical isolation, I/O rail	4 kV	electrical isolation, input-earth	1.5 kV
electrical isolation, input-output	3 kV	electrical isolation, output-earth	0.5 kV

**Connection data**

Clamping range, nom.	4 mm <sup>2</sup>	Clamping range, min.	0.08 mm <sup>2</sup>
Clamping range, max.	4 mm <sup>2</sup>		

**Approvals**

Approvals institutes	UL508; CSA; Cl. I Div. 2; GOSTME25; CE
----------------------	--

**CP SNT 24W 24V 1A**

Weidmüller Interface GmbH & Co. KG  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
www.weidmueller.com

**Technical data****Classifications**

eClass 6.0	27-04-90-04
------------	-------------

**Notes**

Note, technical data	Derating loss: 33% @ 60°C The internal varistor found in a switch-mode power supply does not replace the need for surge protection within a system.
----------------------	---

CP SNT 24W 24V 1A

Weidmüller Interface GmbH & Co. KG  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
www.weidmueller.com

Drawings

Electric symbol

---

