

CliQ Din Rail Power Supply

12V 60W 1 Phase

DRP012V060W1AA



DRP012V060W1AA

60Watts

Total Power: 60Watts
 Input Voltage: 85-264Vac
 # of Output: Single



Model number DRP012V060W1AA

Reference no. EOE11010159

OUTPUT (DC)

Output power 60W

Output voltage range 11-14V

Output current 5A (60W max.)

Residual ripple/peak switching (20MHz) (à nominal values) < 100mV

Mains buffering at nominal load (typ.) > 22ms @ 115Vac, > 110ms @ 230Vac

Line regulation < 0.5% typ. (@ 85 - 264Vac input, 100% load)

Load regulation < 1% Typical (with rated input, 0 to 100% load)

INPUT (AC)

Input voltage range 85 - 264Vac (DC input range 120 - 375Vdc)

Input frequency 47 - 63Hz

Nominal current 1.65A Max (1.35A @ 115Vac & 0.8A @ 230Vac)

Efficiency Min 85.5% @ 115Vac & 230Vac

Power factor Conform to EN61000-3-2 STD

Inrush current limitation I²t (+25°C) typ. < 50A @ 115Vac, < 100A @ 230Vac

Leakage current < 1mA

MECHANICAL DESIGN

Case cover Aluminium (Al5052)

Dimensions (L x W x H) 121mm x 32mm x 120mm

Unit weight / box 0.325kg

MTBF > 300,000 hrs

Noise Sound pressure level (SPL) < 40dBA

Cooling Convection

Input terminal M4 x 3

Output terminal M4 x 2

Mounting rail Standard TS35 mounting rail

Shock proof IEC60068-2-27

Vibration IEC60068-2-6

Protection structure EN60950 meet IPX0

Special Features

- Ease of multiple wire connection
- Compact design for easy handling
- Overload protection
- Thermal protection
- Power boost 150% for 3secs
- Expected life time: 10 years
- Redundancy: Yes (with external ORing diode)
- RoHS compliant




CliQ Din Rail Power Supply

12V 60W 1 Phase

DRP012V060W1AA

MECHANICAL DRAWING



Delta Electronics (Thailand)
Public Company Limited
909 Moo 4, E.P.Z.,
Bangpoo Industrial Estate,
Tambon Prakasa, Amphur
Muang Samutprakarn,
Samutprakarn 10280, Thailand
Tel: +662 709 2800
Fax: +662 709 2827
E-mail: VL@delta.co.th
www.deltaenergysystems.com

SAFETY / ENVIRONMENTAL

EMC / Emissions	EN61000-3-2, 3 : 1995/A1 : 2001/A2 : 2005, EN55022 : 2006 Class B, EN55011 : 1998/A2 : 2002 Class B, EN6100-6-1 (IEC61000-4-2, 3, 4, 5, 6, 8, 11)
Immunity	EN61000-6-2, EN55024, EN61000-4-2, IEC61000-4-3, 4, 5, 6, 8, 11
Safety standard	UL Listed for UL508 & CSA 22.2 no.107.1-01, UL Recognized for UL60950-1 & CSA 22.2 no.60950-1, UL60950-1 and CSA 22.2 no.107.1-01, TUV Bavart Mark to EN60950-1, EN50178 : 1998, IEC60204-1 : 1998 & IEC62103 : 2003, CB cert from TUV to IEC60950-1, CE (EMC and Low Voltage directive) , CCSAUS to CSA 22.2 no.60950-1
Voltage dips	Conforms to EN61000-4-11
Galvanic isolation	Input to output: 4KVac; Input to ground: 1.5KVac; Output to ground: 1.5KVac
Operating ambient temperature	-20°C ~ 75°C *
Storage temperature	-25°C ~ 85°C
Operating humidity	< 95%
Note (*)	Operating amb. > 50°C derate power by 2.5% / °C; Operating amb. > 70°C derate power by 4% / °C