



**Features:**

- Open frame
- Fully isolated output
- Input/output isolation: 1500 VAC
- Warranty – 5 years

**Environmental**

- Operating temperature....0° C to 40° C
- Storage temperature.....-55° C to 85° C

**EMI**

Meets FCC class B, CISPR 22 class B

**Safety**

UL recognized

**Electrical specifications**

**Input**

- Voltage.....105/115/125 VAC
- Frequency.....47-400 Hz
- Input connector.....Transformer lugs

**Output**

- Unregulated: +/-10% full load
- Ripple/noise +/-3% RMS, DC to 50MHz

**Mechanical:**

- Size: 8.1 x 3.9 x 5.0 inches
- Weight: 12 lbs

**Specifications:**

| Elpac Part # | Vdc | Amps | Watts | No load | Full load |
|--------------|-----|------|-------|---------|-----------|
|              |     |      |       | Volts   | Volts     |
| BFS200-12    | 12  | 15   | 200   | 15.4    | 12.5      |
| BFS200-20    | 20  | 10   | 200   | 24.5    | 20        |
| BFS200-24    | 24  | 7.5  | 200   | 32.2    | 27.3      |
| BFS200-48    | 48  | 4    | 200   | 55.2    | 46.4      |



ELPAC POWER SYSTEMS (949) 476-6070, www.elpac.com, sales@elpac.com