

MINI-BAT/24DC/1.3AH

Order No.: 2866417

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2866417>

Rechargeable battery module, 24 V DC, 1.3 Ah, for use with MINI-UPS/2A and TRIO-UPS/5A

Commercial data	
EAN	4046356152112
Pack	1 pcs.
Customs tariff	85072098
Weight/Piece	2.159 KG
Catalog page information	Page 592 (IF-2009)

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
Input data	
Nominal input voltage	24 V DC
Output data	
Nominal output voltage	24 V DC
Output current	max. 15 A
Connection in series	No
Output fuse	15 A
General data	
Width	52 mm
Height	130 mm

Depth	110 mm
Weight	1.7 kg
Degree of protection	IP20
Class of protection	III
Ambient temperature (operation)	0 °C ... 40 °C
Ambient temperature (storage/transport)	0 °C ... 40 °C

Accessories

Item	Designation	Description
Fuse		
0913676	SI FORM C 15 A DIN 72581	Fuse modular terminal block, Nominal current: 15 A, Length: 19 mm, Width: 5 mm, Height: 13 mm, Color: light blue

Diagrams/Drawings

Block diagram



Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;