

AE-TS56-16I



DIP40/TSOP56 specialized adapter for FLASH memory.
 Device package dimensions: 14 x 20 mm, 0.5 mm pitch.

Click the programmer model below to get an appropriate list of the devices supported by the adapter:

- [ChipProg+](#)
- [ChipProg-40](#)
- [ChipProg-48, ChipProg-G4](#)

Adapter Wiring Diagram:

DIP-40	TSOP-56	U1, 74AHC573	U2, 74AHC573	C1, 150pF	C2, 0.1uF
1	43				
2	2				
3		11	11	1	
4	16				
7	55				
8	53				
9	15				
10	20				
11	22				
12	23				
13	24				
14	25				
15	26				
16	27				

17	28				
18	32				
19	29				
20	21,42,48	1, 10	1, 10	2	2
21	14				
22	54				
23	33	2			
24	34		2		
25	35	3			
26	36		3		
27	38	4			
28	39		4		
29	40	5			
30	41		5		
31	44	6			
32	45		6		
33	46	7			
34	47		7		
35	49	8			
36	50		8		
37	51	9			
38	52		9		
39	31				
40	9.37	20	20		1
	1		14		
	3		15		
	4		16		
	5		17		
	6		18		
	7		19		
	8	12			
	10	13			
	11	14			
	12	15			
	13	16			
	17	17			
	18	18			
	19	19			
	30		13		
	56		12		