


AE-B64-SP2

DIP40/BGA64 specialized adapter for FLASH memory.
 Device package dimensions: 13.0 x 10.0 x 1.2 mm, 1.0 mm pitch.



Click the programmer model below to get an appropriate list of the devices supported by the adapter:

- [ChipProg+](#)
- [ChipProg-40](#)
- [ChipProg-48, ChipProg-G4](#)

Adapter Connection Table:

DIP-40	BGA-64	U1, 74HC573	U2, 74HC573	C1, 150pF	C2, 0.1uF
1	D5,D6				
2	B8				
3		11	11	1	
4	D4				
5					
6					
7	G8				
8	E8				
9	A4				
10	A3				
11	C2				
12	A2				
13	D2				
14	D1				
15	C1				
16	B1				
17	A1				
18					
19	H1				

AE-B64-SP2

20	E6,F6,B2,H4,H6	1, 10	1, 10	2	2
21	B4				
22	F8				
23	F2	2			
24	E1		2		
25	E2	3			
26	E3		3		
27	G3	4			
28	F3		4		
29	E4	5			
30	F4		5		
31	E5	6			
32	F5		6		
33	G5	7			
34	H5		7		
35	G6	8			
36	G7		8		
37	H7	9			
38	E7		9		
39	F1				
40	C6,H3,G4,A6	20	20		1
	H8		12		
	G1		13		
	D7	12			
	C5	13			
	B5	14			
	A5	15			
	C4	16			
	D3	17			
	C3	18			
	B3	19			
	C7		16		
	C8		15		
	A8		14		
	B7		17		
	A7		18		
	D8		19		