

**M68EVB912D60
EVALUATION BOARD
USER'S MANUAL**

2nd Edition

© MOTOROLA Inc., 1999; All Rights Reserved

**For More Information On This Product,
Go to: www.freescale.com**

Motorola reserves the right to make changes without further notice to any products herein to improve reliability, function or design. Motorola does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part.

* Cautionary Note *

EMC Information on M68EVB912D60

This product conforms with the protection requirements of Council Directive 89/336/EEC of 3 May 1989 on the approximation of the laws of the Member States relating to electromagnetic compatibility.

(Directive 89/336/EEC amended by Directives 91/263/EEC, 92/31/EEC, 93/68/EEC, 93/97/EEC)

1) This is a Class A product.

In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

2) Anti-static precautions must be adhered to when using this product.

3) Connecting any signal cable to this product may affect its performance and also Cause interference with other apparatus in the immediate vicinity. If it is necessary to make any such connections suitable mitigating measures should be taken.

1. Introduction

This manual provides the necessary information for using the M68EVB912D60 Evaluation Board (EVB), an evaluation and debugging tool for the MC68HC912D60 Microcontroller Unit (MCU) device. The manual includes a general description of the EVB as well as configuration and set-up instructions

2. General Description and Features

The EVB can be used in conjunction with an appropriate debugger tool that uses the background debug mode, such as Motorola's (or Noral's) Serial Debug Interface (SDI), and compatible debug software such as Motorola's MCUEz or P&E's SDBUG12.

The board consists of a 4 layer PCB which provides the interface and power connections to the MC68HC912D60 microcontroller (MCU).

Hardware features include the following:

- Single 5 V dc power supply connector
- RS-232C Interface
- BDM In connector providing interface to Background Debug Mode
- 16 MHz oscillator module
- Prototype expansion area for customised interfacing with the MCU
- Low-voltage inhibit protection
- CAN Physical Interface
- Chargepump for the supply of the flash programming voltage
- Bargraph LED to assist with debugging
- 8 way DIP switch to assist with debugging

The EVB is factory configured to start in single chip or special single chip mode. It is supplied with the flash EEPROM unprogrammed and can be run with an appropriate debugger, via the Background Debug Mode (BDM) interface.

The EVB features a prototype area, which allows custom interfacing with the MCU's I/O and bus lines. The MCU pins can be accessed via header footprints immediately adjacent to the MCU.


An on-board push-button switch, S2, allows the EVB hardware to be manually reset.

A CAN physical interface is provided on the board. This comprises of a Philips PCA82C250 CAN Interface controller.

3. Hardware Reference

3.1 Power Supply

The EVB requires an external +5 volt power supply for operation. Ideally this should be current limited to 200mA. Power is supplied to the EVB via the power socket, P6. A 2.5mm power plug has been included in the M68EVB912D60 kit to allow the user to power the EVB from a standard desktop power supply. To do this the user should solder insulated wires onto the two terminals of the power plug, and then connect the other ends of the wires up to their power supply. Great care should be taken to ensure that the 5 Volt supply is connected to the internal part of the power plug and the Gnd supply is connected to the external barrel of the power plug.



3.2 BDM In Connector

The EVB can be used in conjunction with a suitable Background Debug Mode (BDM) debugger interface, such as the SDI, and appropriate debugger software. The BDM input to the EVB is via jumper J16. Table 3-1 shows the pinout for J16.

3.3 MCU Operating Mode

Jumpers J24 and J25 allow the user to select which mode the MCU starts in after reset by controlling the state of the MODA and MODB pins. The default mode is to pull the MCU MODA and MODB pins to ground. This results in the MCU starting from reset in either Single Chip or Special Single Chip mode (dependant on the state of the BKGD pin).

The state of the MODA and MODB pins can also be set via the Noral SDI cable. When this option is used it is not necessary to install links on jumpers J24 and J25.

3.4 Clock

A 16 MHz oscillator module provides the clock signal to the MCU. Jumper J27 must be installed between pins 1 and 2 (factory default) to configure the clock signal correctly.

3.5 RS-232C Interface

An RS-232C interface is provided on the EVB through a 9 way D type connector, P1. Signal level translation between the MCU and P1 is provided by an MC145407 RS-232 interface IC (U3) . This is connected to the TxD and RxD pins of the Serial Communications Interface (SCI) on the MC68HC912D60 via jumpers J11 (TxD) and J9 (RxD). As there are two serial communications interface modules supplied on the MCU, jumpers J9 and J11 can be used to select between them. The EVB has been configured to act as Data Circuit-terminating Equipment (DCE). Removing jumpers J8, J10 and J13 allows the user to disable this function if it is not required.

3.6 CAN Physical Interface


There is a CAN physical interface supplied on the M68EVB912D60. The CAN physical interface comprises a Philips PCA82C250 CAN Interface controller (U1). The TXD and RXD pins on the PCA82C250 are connected to the CANTX and CANRX pins on the MC68HC912D60 respectively. The CAN bus signals, CANH and CANL are available on jumper J1. Table 3-1 shows the pinout for J1.

3.7 Programming Operation

It is possible to configure the M68EVB912D60 as a programming tool. To do this the relevant programming adapter board has to be purchased (contact Motorola for further details). To configure the EVB as a programming tool, the adapter board has to be connected to the header strips on the EVB (when doing this care should be taken to ensure that the adapter board is installed with the correct polarity as failure to do so could result in damage to the device being programmed). It is also necessary to install the jumpers on header P8 in the PGMR position.

There are two possible ways of supplying the flash EEPROM programming voltage V_{FP} to the MCU, either via the MAX662 chargepump I.C. (U5), or via the SDI cable. The source of the flash EEPROM programming voltage can be selected via jumper J17.


There is an option for controlling the operation of the chargepump I.C. (U5). If there is no jumper link installed on Jumper J14, then the V_{FP} supply will be held at the level of V_{DD} . If a jumper link is installed on Jumper J14 then 12V will be supplied to the V_{FP} pin of the MCU. In addition to this there is an option which allows the user to control the operation of the chargepump I.C. via a port pin of their choice. To do this the user must connect a wire between the pad situated to the right hand side of Jumper J14 and the pad of the port pin they want to use as the controller. When this option is chosen the user must remove the jumper link from jumper J14.




3.8 Jumper Configuration

Table 3-1 summarises the jumper and header configurations for the EVB.

Key to Table 3-1

 2 pin header with no jumper installed

 2 pin header with jumper installed

 3 pin header with jumper installed between pins 1 and 2

 3 pin header with jumper installed between pins 2 and 3




































 3 pin header with no jumper installed




Table 3-1 - Jumper and Header Functions

(Default factory configurations shown as **bold type**)

Diagram	Pins	Description
J1 - CAN Physical Interface Connector		
	1 2 3 4 5 6 7 8	GND GND CANH CANH CANL CANL GND GND
J2 - CAN1 Physical Interface Connector (Not fitted on D60EVB)		
	1 2 3 4 5 6 7 8	GND GND CANH CANH CANL CANL GND GND
J3 - VRH1 Voltage Select		
	In	Connects VRH1 pin to VCC
J4 - CAN1 Physical Interface 120 Ohm termination impedance (Not fitted on D60EVB)		
	In	Connects 120 Ohm termination impedance to CAN1 bus
J5 - CAN Physical Interface 120 Ohm termination impedance		
	In	Connects 120 Ohm termination impedance to CAN bus
J6 - VRL1 Voltage Select		
	In	Connects VRL1 pin to GND
J7 - Port G - Pull Up/Down Select (D60 Only)		
	1 - 2 2 - 3	Port G pulled to VCC via 47K Port G pulled to GND via 47K

J8/J10/J13 - RS-232 Configuration (DCE)		
J13 	In	
J8 	In	
J10 	In	
J9 - SCI RxD Module Select		
PS0  PS2	PS0 PS2	Rxd0 connected to RS-232 Interface Rxd1 connected to RS-232 Interface
J11 - SCI TxD Module Select		
PS1  PS3	PS1 PS3	Txd0 connected to RS-232 Interface Txd1 connected to RS-232 Interface
J12 - VDDAD Supply		
ON  OFF	ON OFF	VDDAD pin connected to VCC VDDAD pin connected to GND
J14 - MAX662A Shutdown Voltage Source Select		
VFP ENABLE 	In Out	12V supplied to VFP pin VFP pin held at VCC
J15 - IDD Measurement		
	In	For factory test purposes only
J16 - BDM In		
1  2 5  6	1 2 3 4 5 6	BKGD GND No Connect *RESET EXTVPP VCC
J17 - VFP Source Select		
ICVPP  SDIVPP	ICVPP SDIVPP	VFP supplied from chargepump I.C. (U5) VFP supplied via Noral SDI cable
J18 - VRL0 Voltage Select		
	In	Connects VRL0 pin to GND

J19 - VRH0 Voltage Select												
	In	Connects VRH0 pin to VCC										
J20 - Noral SDI Connector												
<table border="0"> <tr> <td style="padding-right: 5px;">1</td> <td style="text-align: center;"></td> <td style="padding-right: 5px;">2</td> </tr> <tr> <td style="padding-right: 5px;">3</td> <td style="text-align: center;"></td> <td style="padding-right: 5px;">4</td> </tr> </table>	1		2	3		4	<table border="0"> <tr><td>1</td></tr> <tr><td>2</td></tr> <tr><td>3</td></tr> <tr><td>4</td></tr> </table>	1	2	3	4	MODA MODB GND ECLK
1		2										
3		4										
1												
2												
3												
4												
J21 - VDDPLL Supply												
ON  OFF	ON OFF	VDDPLL pin connected to VCC VDDPLL pin connected to GND										
J22 - D60 /DG128 Selection Jumper												
DG128  D60	DG128 D60	RAM standby voltage connected to VCC (DG128 only) Port H pull up/pull down select (D60 only)										
J23 - Port H - Pull Up/Down Select (D60 Only)												
1 	1 - 2 2 - 3	Port H pulled to VCC via 47K Port H pulled to GND via 47K										
J24 - MODA Pull Up/Down Select												
1 	1 - 2 2 - 3	MODA pulled to VCC via 47K. MODA pulled to GND via 47K.										
J25 - MODB Pull Up/Down Select												
1 	1 - 2 2 - 3	MODB pulled to VCC via 47K. MODB pulled to GND via 47K.										
J26 - XTAL Select												
	Out	Connect external crystal circuit to XTAL pin										
J27 - EXTAL - Clock source select												
FROM U6  FROM Y1	1 - 2 2 - 3	Connect U6 (Osc. Module) output to EXTAL Connect external crystal circuit to EXTAL										
J29 – PAD0 – Pull Up/Down Select (For future expansion)												
ON  OFF	ON OFF	PAD0 pulled to VCC via 15K PAD0 pulled to GND via 15K										

J30 – PAD1– Pull Up/Down Select (For future expansion)		
ON  OFF	ON OFF	PAD1 pulled to VCC via 15K PAD1 pulled to GND via 15K
P4 – Connection to Bargraph LED		
	IN IN IN IN IN IN IN IN	PB0 connected to LED PB1 connected to LED PB2 connected to LED PB3 connected to LED PB4 connected to LED PB5 connected to LED PB6 connected to LED PB7 connected to LED
P8 – EVB/PGMR Selection Jumper		
	EVB EVB EVB EVB EVB EVB EVB	

