



[Home](#)

[Embedded Software](#)

[Development Tools](#)

[Production Tools](#)

[Flasher ARM](#)
[Flasher 5](#)

[Flasher ST7](#)

[Installing / Using Software](#)
[Supported Microcontrollers](#)

[Evaluate our software!](#)

[Downloads](#)

[Distributors](#)
[Customers](#)

[Partners](#)

[Sales](#)

[Forum](#)

[About us](#)

[Head office Germany](#)

Phone: +49-2103-2878-0
Fax: +49-2103-2878-28
E-mail info@segger.com
www.segger.com

[US office](#)

Phone: +1-978-874-0293
Fax: +1-978-874-0599
E-mail info@segger-us.com
www.segger-us.com



[Production Tools](#) [Flasher ST7](#) [Overview](#)

Flasher ST7

Features

- Small, compact housing
- Easy to use windows program
- Serial (in target) programming supported
- Programming / Verifying / Read back supported
- OPTION BYTE Programming supported
- 512 KByte internal Flash memory to store target program
- High speed programming: app 12 sec for 60 kb in serial mode with 16 MHz target clock for programming and verification
- Can be used in a production environment
- PC program allows batch mode processing for usage in automated test systems.
- Once set up, Flasher can be controlled without the use of PC program
- ASCII comm and interface to control Flasher without the use of PC program (Requires firmware version 1.84 or above)



[Documentation download](#)



[Subscribe to Flasher 5/ST7 software notification](#)

[Imprint](#) [Disclaimer](#) [Sitemap](#)

[back to top](#)