

## Chip Resistor Array

- Type: **EXB1 : 0201 Array**  
**EXB2 : 0402 Array**  
**EXB3 : 0603 Array**  
**EXBN : 0402 Array**  
**EXBV : 0603 Array**  
**EXBS : 0805 Array**



### ■ Features

- High density
  - 2 resistors in 0.8 mm × 0.6 mm size (EXB14V)
  - 4 resistors in 1.4 mm × 0.6 mm size (EXB18V)
  - 2 resistors in 1.0 mm × 1.0 mm size (EXB24V)
  - 4 resistors in 2.0 mm × 1.0 mm size (EXB28V, N8V)
  - 8 resistors in 3.8 mm × 1.6 mm size (EXB2HV)
  - 2 resistors in 1.6 mm × 1.6 mm size (EXB34V, V4V)
  - 4 resistors in 3.2 mm × 1.6 mm size (EXB38V, V8V)
  - 4 resistors in 5.1 mm × 2.2 mm size (EXBS8V)

### ■ Packaging Methods

Please see Pages 40 to 43

### ■ Recommended Land Pattern

Please see Pages 44 to 45

### ■ Recommended Soldering Conditions

Please see Page 46

### ■ Safety Precautions

Please see Page 47

### ● Improvement of placement efficiency

Placement efficiency of Chip Resistor Array is two, four or eight times of the flat type chip resistor

### ● Reference Standard... IEC 60115-9, JIS C 5201-9, EIAJ RC-2129

### ■ Explanation of Part Numbers



### ■ Construction (Example : Concave Terminal)



### ■ Schematics

#### ● Isolated type



Design and specifications are each subject to change without notice. Ask factory for the current technical specifications before purchase and/or use. Should a safety concern arise regarding this product, please be sure to contact us immediately.

## ■ Dimensions in mm (not to scale)

### (1) Convex Terminal type



| Type<br>(inch size) | Dimensions (mm)       |                       |                       |                       |                       |                       |        |                       | Mass (Weight)<br>[g/1000 pcs.] |
|---------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|--------|-----------------------|--------------------------------|
|                     | L                     | W                     | T                     | A1                    | A2                    | B                     | P      | G                     |                                |
| EXB14V (0201×2)     | 0.80 <sup>±0.10</sup> | 0.60 <sup>±0.10</sup> | 0.35 <sup>±0.10</sup> | 0.35 <sup>±0.10</sup> | —                     | 0.15 <sup>±0.10</sup> | (0.50) | 0.15 <sup>±0.10</sup> | 0.5                            |
| EXB24V (0402×2)     | 1.00 <sup>±0.10</sup> | 1.00 <sup>±0.10</sup> | 0.35 <sup>±0.10</sup> | 0.40 <sup>±0.10</sup> | —                     | 0.18 <sup>±0.10</sup> | (0.65) | 0.25 <sup>±0.10</sup> | 1.2                            |
| EXB28V (0402×4)     | 2.00 <sup>±0.10</sup> | 1.00 <sup>±0.10</sup> | 0.35 <sup>±0.10</sup> | 0.45 <sup>±0.10</sup> | 0.35 <sup>±0.10</sup> | 0.20 <sup>±0.10</sup> | (0.50) | 0.25 <sup>±0.10</sup> | 2.0                            |
| EXB2HV (0402×8)     | 3.80 <sup>±0.10</sup> | 1.60 <sup>±0.10</sup> | 0.45 <sup>±0.10</sup> | 0.35 <sup>±0.10</sup> | 0.35 <sup>±0.10</sup> | 0.30 <sup>±0.10</sup> | (0.50) | 0.30 <sup>±0.10</sup> | 9.0                            |
| EXB34V (0603×2)     | 1.60 <sup>±0.20</sup> | 1.60 <sup>±0.15</sup> | 0.50 <sup>±0.10</sup> | 0.65 <sup>±0.15</sup> | —                     | 0.30 <sup>±0.20</sup> | (0.80) | 0.30 <sup>±0.20</sup> | 3.5                            |
| EXB38V (0603×4)     | 3.20 <sup>±0.20</sup> | 1.60 <sup>±0.15</sup> | 0.50 <sup>±0.10</sup> | 0.65 <sup>±0.15</sup> | 0.45 <sup>±0.15</sup> | 0.30 <sup>±0.20</sup> | (0.80) | 0.35 <sup>±0.20</sup> | 7.0                            |

### (2) Concave Terminal type

( ) Reference



| Type<br>(inch size) | Dimensions (mm)             |                             |                       |                       |                       |                       |        |                       | Mass (Weight)<br>[g/1000 pcs.] |
|---------------------|-----------------------------|-----------------------------|-----------------------|-----------------------|-----------------------|-----------------------|--------|-----------------------|--------------------------------|
|                     | L                           | W                           | T                     | A1                    | A2                    | B                     | P      | G                     |                                |
| EXBN8V (0402×4)     | 2.00 <sup>±0.10</sup>       | 1.00 <sup>±0.10</sup>       | 0.45 <sup>±0.10</sup> | 0.30 <sup>±0.10</sup> | 0.30 <sup>±0.10</sup> | 0.20 <sup>±0.15</sup> | (0.50) | 0.30 <sup>±0.15</sup> | 3.0                            |
| EXBV4V (0603×2)     | 1.60 <sup>+0.20/-0.10</sup> | 1.60 <sup>+0.20/-0.10</sup> | 0.60 <sup>±0.10</sup> | 0.60 <sup>±0.10</sup> | —                     | 0.30 <sup>±0.15</sup> | (0.80) | 0.45 <sup>±0.15</sup> | 5.0                            |
| EXBV8V (0603×4)     | 3.20 <sup>+0.20/-0.10</sup> | 1.60 <sup>+0.20/-0.10</sup> | 0.60 <sup>±0.10</sup> | 0.60 <sup>±0.10</sup> | 0.60 <sup>±0.10</sup> | 0.30 <sup>±0.15</sup> | (0.80) | 0.45 <sup>±0.15</sup> | 10                             |
| EXBS8V (0805×4)     | 5.08 <sup>+0.20/-0.10</sup> | 2.20 <sup>+0.20/-0.10</sup> | 0.70 <sup>±0.20</sup> | 0.80 <sup>±0.15</sup> | 0.80 <sup>±0.15</sup> | 0.50 <sup>±0.15</sup> | (1.27) | 0.55 <sup>±0.15</sup> | 30                             |

### (3) Flat Terminal type

( ) Reference



| Type<br>(inch size) | Dimensions (mm)       |                       |                       |                       |                       |                       |        |                       | Mass (Weight)<br>[g/1000 pcs.] |
|---------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|--------|-----------------------|--------------------------------|
|                     | L                     | W                     | T                     | A1                    | A2                    | B                     | P      | G                     |                                |
| EXB18V (0201×4)     | 1.40 <sup>±0.10</sup> | 0.60 <sup>±0.10</sup> | 0.35 <sup>±0.10</sup> | 0.20 <sup>±0.10</sup> | 0.20 <sup>±0.10</sup> | 0.10 <sup>±0.10</sup> | (0.40) | 0.20 <sup>±0.10</sup> | 1.0                            |

( ) Reference

Design and specifications are each subject to change without notice. Ask factory for the current technical specifications before purchase and/or use.  
Should a safety concern arise regarding this product, please be sure to contact us immediately.

00 Sep. 2010

### ■ Ratings

| Item                  |                         | Specifications                      |
|-----------------------|-------------------------|-------------------------------------|
| Resistance Range      |                         | 10 Ω to 1 MΩ: E24 series            |
| Resistance Tolerance  |                         | J: ±5 %                             |
| Number of Terminals   | 14V,24V,V4V,34V         | 4 terminal                          |
|                       | 18V,28V,N8V,38V,V8V,S8V | 8 terminal                          |
|                       | 2HV                     | 16 terminal                         |
| Number of Resistors   | 14V,24V,V4V,34V         | 2 terminal                          |
|                       | 18V,28V,N8V,38V,V8V,S8V | 4 terminal                          |
|                       | 2HV                     | 8 terminal                          |
| Power Rating at 70 °C | 14V,N8V                 | 0.031 W/element                     |
|                       | 18V                     | 0.031 W/element<br>(0.1 W/package)  |
|                       | 24V,28V,V4V,34V,V8V,38V | 0.063 W/element                     |
|                       | S8V                     | 0.1 W/element                       |
|                       | 2HV                     | 0.063 W/element<br>(0.25 W/package) |

| Item                                    |                             | Specifications                  |       |
|---|-----------------------------|---------------------------------|-------|
| Limiting Element Voltage <sup>(1)</sup> | 14V,18V                     | 12.5 V                          |       |
|   | 2HV                         | 25 V                            |       |
|   | 24V,28V,N8V,38V,34V,V4V,V8V | 50 V                            |       |
| Max. Over-load Voltage <sup>(2)</sup>   | S8V                         | 100 V                           |       |
|   | 14V,18V                     | 25 V                            |       |
|   | 2HV                         | 50 V                            |       |
| T.C.R.                                  | 24V,28V,N8V,38V,34V,V4V,V8V | 100 V                           |       |
|   | S8V                         | 200 V                           |       |
| T.C.R.                                  |                             | ±200×10 <sup>-6</sup> /°C       |       |
| Category Temperature Range              |                             | -55 °C to 125 °C                |       |
| Jumper Array                            | Rated Current               | 14V,18V                         | 0.5 A |
|   |                             | 2HV,24V,28V,N8V,38V,34V,V4V,V8V | 1 A   |
|   |                             | S8V                             | 2 A   |
|   | Max. Overload Current       | 14V,18V                         | 1 A   |
|   |                             | 2HV,24V,28V,N8V,38V,34V,V4V,V8V | 2 A   |
|   | S8V                         | 4 A                             |       |

(1) Rated Continuous Working Voltage (RCWV) shall be determined from  $RCWV = \sqrt{\text{Power Rating} \times \text{Resistance Value}}$ , or Limiting Element Voltage listed above, whichever less.

(2) Overload (Short-time Overload) Test Voltage (SOTV) shall be determined from  $SOTV = 2.5 \times \text{Power Rating}$  or max. Overload (Voltage) listed above whichever less.

### Power Derating Curve

For resistors operated in ambient temperature above 70 °C, power rating shall be derated in accordance with the figure on the right.

