THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-Z-HOOK. THE INFORMATION IS NOT TO BE REPRODUCED WITHOUT PRIOR WRITTEN PERMISSION OF E-Z-HOOK, DIV. OF TEKTEST INC.
MAXIMUM TESTED RATINGS IN A HANDS-FREE CONTROLLED ENVIRONMENT. MAXIMUM RATINGS ARE NOT TO BE USED CONCURRENTLY. <u>ب</u> 5 NOTES: UNLESS OTHERWISE SPECIFIED **NEXT ASSY** P/N: W-600/COLOR P/N: 9260COLOR PERFORMANCE 0.144 [3.66] O.D. PVC INSULATION AVAILABLE IN TEN COLORS. FRAME: BRASS. NICKEL PLATED. MAXIMUM TEMPERATURE: 221°F (105°C) CONTACT: BeCu OR PHOSPHOR BRONZE. NICKEL PLATED. HOUSING: MOLDED NYLON. AVAILABLE IN TEN COLORS. MAXIMUM VOLTAGE: 5000 UL W.V.D.C. MAXIMUM CURRENT: 4.0 AMPS 18AWG 65X36 TINNED COPPER **APPLICATION USED ON** SEE NOTE SEE NOTE MATERIAL FINISH UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: FRACTIONS DECIMALS ANGLES DO NOT SCALE DRAWING CONTRACT NO. APPROVED BY DRAWN APPROVALS 둤 10/10 STK BANANA PLUG (9260) SIZE CODE IDENT NO. DRAWING NO. SCALE EZHOOK DIVISION OF TEKTEST INC. |08505|9111 DESCRIPTION 0.562 [14.26] 1.630 [41.40] REVISIONS SHEET 1 OF 0.175 [4.45] APPROVED REVE