



## MATERIALS:

### *Retractable Sheath Banana Plug:*

- Plug Body: Gold Plated Tellurium Copper
- Banana Spring: Gold Plated Beryllium Copper
- Compression Spring: Stainless Steel
- Tip: Nylon, Color Matches Color of Wire

*Insulation:* Nylon Molded to the Plug and Wire. Color Matches Color of Wire.

*Wire:* 12 AWG, Stranding 10 x 26/36 Bare Copper, PVC Insulated, .144" (3,66mm) O.D.

## RATINGS:

- Operating Temperature: +131° F (+55° C) Max.
- Operating Voltage: 1000V Category III, IEC1010-2-031
- Current: 7 Amperes

## ORDERING INFORMATION:

Model 5291A-**\*Length-Color**

**Length** =: 12" (30,48cm), 36" (91,44cm) & 60" (152,4cm)

**Color** = 0 (Black), 2 (Red)

Ordering Example: 5291A-12-2 (red 12" patch cord).

\* For custom lengths, email [custom@pomonatest.com](mailto:custom@pomonatest.com).

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Support: 800-241-2060 ([technicalsupport@pomonatest.com](mailto:technicalsupport@pomonatest.com))  
For "Where to Buy" information, visit the Pomona web site at [www.pomonaelectronics.com](http://www.pomonaelectronics.com)