



**FEATURES:**

- ✓ Modular Test Probe
- ✓ Replaceable tip
- ✓ Comes with two Stainless-Steel Sharp Point Tips: Model 4172

**MATERIALS:**

Replaceable Tip Probe: Stainless Steel  
 Tip O.D.: 0.080"  
 Body: Nylon

**RATINGS:**

Operating Voltage: 600 Vrms per IEC2020-2-031, Category III.  
 Operating Current: 10 Amperes

**ORDERING INFORMATION:**

Model 5689A

**Replaceable Tips:**

- Model 5688: Standard
- Model 4172: Stainless-Steel Sharp Point
- Model 5133: SMD Microtip, Stainless-Steel Sharp Point
- Model 4988: Needle Stainless-Steel Sharp Point
- Model 6364: Set of tips

**Modular Test Leads:**

- Model 5907A: Right-Angle Banana Plug to Straight Banana Plug
- Model 5908A: Straight Banana Plug to Straight Banana Plug
- Model 5909A: Right-Angle Banana Plug to Right-Angle Banana Plug



All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).  
 All specifications are to the latest revisions. Specifications are subject to change without notice.  
 Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Support: 800-241-2060 (technicalsupport@pomonatest.com)  
 For "Where to Buy" information, visit the Pomona web site at [www.pomonaelectronics.com](http://www.pomonaelectronics.com)