THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-Z-HOOK, THE INFORMATION IS NOT TO BE REPRODUCED WITHOUT PRIOR WRITTEN PERMISSION OF E-Z-HOOK, DIV. OF TEKTEST INC.
MAXIMUM TESTED RATINGS IN A HANDS-FREE CONTROLLED ENVIRONMENT. MAXIMUM RATINGS ARE NOT TO BE USED CONCURRENTLY. 2 NOTES: UNLESS OTHERWISE SPECIFIED **NEXT ASSY** CONSTRUCTION: PERFORMANCE: HOUSING: MOLDED NYLON 6 OR 6,6. AVAILABLE IN BLACK, RED, GREEN OR BLUE. CONTACT TIP: STEEL. BRIGHT NICKEL FINISH. MAXIMUM TEMPERATURE: 200°F (93°C) MAXIMUM VOLTAGE: 1000 V MAXIMUM CURRENT: 10 AMPS APPLICATION 0.08 [2.01] -Ø0.875 [Ø22.23] **USED ON** SEE NOTE SEE NOTE MATERIAL FINISH UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: FRACTIONS DECIMALS ANGLES DO NOT SCALE DRAWING 1.56 [39.62] → · XX + — 0.350 [8.89] DRAWN CONTRACT NO. APPROVED BY APPROVALS 둤 5.75 [145.97] -3/09 DATE DESCRIPTION SIZE CODE IDENT NO. DRAWING NO. SCALE EZHOOK DIVISION OF TEKTEST INC. DESCRIPTION 08505 STD PIN TIP PROBE REVISIONS Ø0.175 [Ø4.45]
WIRE EXIT HOLE SHEET 1 OF APPROVED REVE