

102

## Wiha Quality Tools





Toll Free: (800) 494-6104

## Wiha Insulated 3/8" Sockets & Sets



314 95 24 Pc. Insulated 3/8" Drive Socket Set - Inch

CV steel, forged,	oil-hardened sockets. Insulated to EN/IEC 60900.					
Item No. 314 95	Set includes the following:					
	1/4, 9/32, 5/16, 11/32, 3/8, 7/16					
<del></del>	1/2, 9/16, 5/8,11/16, 3/4" Sockets					
lbs. 12856	3/8" x 125mm Extension Bar					
9.07 12857	3/8" x 250mm Extension Bar					
12852	3/8" Ratchet - 190mm					
15000	Insulated Electrician's Knife - 50mm					
Slotted: 3.5, 4.5, 6.5mm						
Phillips: 1, 2, 3						
32806 6.3" Long Nose Pliers						
32818	8.0" Combo Pliers					
32832	6.3" Diagonal Cutters					

<sup>\*</sup>Sockets must be used with insulated ratchets & extensions



CV steel forged oil-hardened sockets. Insulated to EN/IEC 60000

CV steel,	iorgea, c	oli-nardened sockets. Insulated to EIV/IEC 60900.
Item No. 3	315 92	Set includes the following:
		6, 7, 8, 9, 10, 11, 12,
<b>↓</b>		13, 14, 17, 19mm Sockets
lbs.	12856	3/8" x 125mm Extension Bar
9.08	12857	3/8" x 250mm Extension Bar
	12852	3/8" Ratchet - 190mm
	15000	Insulated Electrician's Knife - 50mm
	Slotted	: 3.5, 4.5, 6.5mm
	Phillips	: 1, 2, 3
	32806	6.3" Long Nose Pliers
	32818	8.0" Combo Pliers
	32832	6.3" Diagonal Cutters

<sup>\*</sup>Sockets must be used with insulated ratchets & extensions





128 52 Insulated 3/8" Drive Ratchet, EN/IEC 60900

Chrome-Vanadium steel. Reversible.							
Item		OAL	OAL	•••			
No.	Inch	mm	Inch	lbs.	pkg.		
128 52	3/8"	190	7.5	.87	1		



Chrome-Vanadium steel.

Item		OAL	OAL	<b>↓</b>		
No.	Inch	mm	Inch	lbs.	pkg.	
128 56	3/8"	125	4.9	.29	1	
128 57	3/8"	250	9.8	.57	1	



290 09 Insulated 3/8" Drive T-handle

Insulation according to EN/IEC 60900 specification, up to 1000 Volt Rated. Individually Tested. Blade chrome-vanadium steel, hardened.

		,			ranaanan otoon, naraonoan
Item	<b>O</b> MM	OAL	OAL	<b>↓</b>	
No.	Inch	mm	Inch	lbs.	pkg.
290 09	3/8	200	7.9"	.55	1

Each tool individually tested to 10,000 volts & certified to 1000 Volt ac or 1500 Volt dc

