

TOOL NUMBER	WIRE SIZE mm ² [AWG]	INSULATION DIAMETER mm [in.]	STRIP LENGTH mm [in.]	CRIMP HEIGHT mm [in.]	CONTACT PART NUMBERS Δ		CONTACT DESCRIPTION	APPLICATION SPECIFICATION
					LOOSE PIECE	STRIP FORM		
91584-1	0.50-1.25 [20-16]	2.10-3.00 [.083-.118]	3.5-4.0 [.138-.157]	1.25-1.37 [.049-.054]	170189-[] 170289-[]	170177-[] 170286-[]	MIC Contacts	114-5004 114-5018
	0.75-1.42 [18-16]	2.16-2.85 [.085-.112]			170222-[]	170221-[]	187 Series FASTON Receptacle	114-5068
	2.00-2.30 [14]	2.60-3.40 [.102-.134]			170467-[]	170466-[]	MIC Contacts	114-5004 114-5018
91586-1	0.50-0.89 [20-18]	2.00-3.43 [.079-.135]	3.5-4.5 [.138-.177]	1.20-1.35 [.047-.053]	172778-[]	172777-[]	MIC MK II Tab Contacts	114-5072
	0.50x2 [20x2]							
	1.25-2.27 [16-14]							
91587-1	0.30-0.56 [22-20]	150-2.20 [.059-.087]	4.0-5.0 [.157-.197]	1.06-1.19 [.042-.047]	170458-[]	170307-[]	MIC Contacts	114-5004 114-5018
	0.75-0.89 [18]	2.20-2.60 [.087-.102]			170459-[]	170308-[]	MIC MK II Tab Contacts	114-5072
91589-1	0.50-1.25 [20-18]	2.1-3.0 [.083-.118]	3.5-4.0 [.138-.157]	1.25-1.37 [.049-.054]	170189-[]	170177-[]	MIC Contacts	114-5004 114-5018
	1.25-2.30 [16-14]	2.6-3.4 [.102-.134]			170222-[]	170221-[]		
91592-1	0.30-0.35 [22]	15-2.0 [.060-.079]	3.5-5.5 [.138-.216]	1.05-1.28 [.041-.050]	172776-[]	172775-[]	MIC MK II Receptacle Contacts	114-5071
	0.50-0.89 [20-18]	2.0-2.6 [.079-.102]						

Δ LIST OF APPLIED CONTACT PART NUMBERS MAY NOT BE COMPLETE AND IS SUBJECT TO CHANGE. FOR CURRENT INFORMATION ON TERMINAL PART NUMBERS, CONTACT THE TOOLING ASSISTANCE CENTER: 1-800-722-1111.

2. AMP, CERTI-CRIMP, FASTON and MIC are trademarks.

DIMENSIONS: mm		CONDUCTANCE UNITS: OPERATING SPECIFICATIONS		AWG	19FEB2002	AMP Tyco Electronics Harrisburg, PA 17105-3400
		-		CH	GULA 19FEB2002	
MATERIAL	FINISH	PLC	PLC	AWG	B. SCHAEFFER 19FEB2002	Certi-Crimp II TOOL DATA SHEET MULTI-INTERLOCK (MIC) CONNECTORS
		1	2			
		3	4	APPLY	19FEB2002	TITLE CASE CODE DRAWING NO
		5	6	WEIGHT		A2 00779 1583008
		7	8	CUSTOMER DRAWING		SCALE SHEET OF REV