


GAGE DIMENSIONS APPLY WHEN TOOL IS  
 BOTTOMED BUT NOT UNDER PRESSURE.

FOR REPLACEMENT OF PARTS OTHER THAN  
 LISTED, TOOL SHOULD BE RETURNED TO OUR  
 FACTORY TO INSURE PROPER CERTI-CRIMP  
 ADJUSTMENT.



"W" DIM.	
GO	.1060
	.082

REVISED	BY	DATE
F-1 REVISED	BS	12-29
E REVISED	BWS/CMT	4-7-74
D REVISED	CM/CMT	3-23
C REVISED	KM/BW	6-15-62

NUMBER	49965
DESCRIPTION	
REQUIRED PER ASSEMBLY	

DATE	4-24-62
BY	[Signature]
DATE	6-15-62
BY	[Signature]

WIRE RANGE - INSULATION	12-10
TOLERANCE EXCEPT SCALE	± .010
CLASS	M B
NO	49965
REV	F-1

REV	F-1
-----	-----

QTY	2	21045-6	RING - RETAINING
	1	300449	PIN - RETAINING
	1	39364	SPRING
	1	39366	COLLAR
	2	300432	PIN - RETAINING
	4	21045-3	RING - RETAINING

HAND TOOL ASSEMBLY

CUSTOMER COPY  
 REFERENCE ONLY

AMP  
 AMP INCORPORATED  
 ARDEN, IOWA

8 7 6 5 4 3 2 1