



1. ORDER REPAIR KIT 125218-4.
- 2.- GAGE DIMENSIONS APPLY WHEN TOOL IS BOTTOMED BUT NOT UNDER PRESSURE.
- 3.- FOR REPLACEMENT OF PARTS OTHER THAN SNAP RINGS OR PINS, TOOL SHOULD BE RETURNED TO OUR FACTORY TO INSURE PROPER CERTI-CRIMP ADJUSTMENT.
- 4.- FOR TOOL USAGE, SEE INSTRUCTION SHEET NO. 1809.

(A)	1	A	39364	SPRING-HANDLE	8
	1	A	300449	PIN-RETAINING	7
	2	A	300387	RING-RETAINING	6
	2	A	300432	PIN-RETAINING	5
	4	-	21045-3	RING-RETAINING	4
	2	A	39207	PIN-ADJUSTMENT	3
	1	B	125083-2	LOCATOR	2
(A)	1	A	3-21016-7	SCREW (#8-32 X 3/8 LFTN.)	1

ENLARGED VIEW OF CRIMPS

"G"		"C"	
GO	NO GO	GO	NO GO
.035	.055	.063 DIA.	.069 DIA.

PINS IN POSITION NO. 1

REV	DESCRIPTION	DATE	BY	CHK	DATE
1	LOC. M WAS A	10/19/61	PP	DR	10/19/61
2	A-1 ADD'D OVERALL DIMS	11/2/61	SR	DR	11/2/61
3	A ADDED 39364 NOTE	11/2/61	DR	DR	11/2/61
4	3-21016-7 WAS	11/2/61	DR	DR	11/2/61
5	39227 & RELOCATED	11/2/61	DR	DR	11/2/61
6	LOC. ITEM # 2	11/2/61	DR	DR	11/2/61
7					

REV	DESCRIPTION	DATE	BY	CHK	DATE
1					
2					
3					
4					
5					
6					
7					

REV	DESCRIPTION	DATE	BY	CHK	DATE
1					
2					
3					
4					
5					
6					
7					

DR	J. J. Jones 10/19/61		
CHK	N. J. Jones 11/2/61		
DE			
APP	C. J. Jones 11/2/61		

1961 BY AMP INCORPORATED. ALL RIGHTS RESERVED.			
AMP PRODUCTS COVERED BY PATENTS AND/OR PATENTS PENDING.			
MATERIAL AND FINISH	STEEL		
FINISH - BLACK OXIDE			
WEIGHT - 1 LBS. 3 OZ.			
WIRE - RANGE - INSULATION	1/2" - 1"		
TOLERANCE EXCEPT AS NOTED	SCALE	LOC	NO
	4	M	B
NAME	DOUBLE ACTION HAND TOOL		

AMP INCORPORATED	HARRISBURG, PENNA.
LONG HANDLES	PRE-INSULATED DIAMOND GRIP
90026	REV A-2

CUSTOMER DRAWING