69872







INSULATION CRIMP BARREL CRIMP

ENLARGED VIEW OF CRIMPS

"G" DIM AT POS. #1		"C" DIM	
GO	NO GO	GO	NO GO
.030	.050	.109	.115



SUGGESTED PLUG GAGE FOR "C" DIM
BARREL CRIMP



SUGGESTED PLUG GAGE FOR "G" DIM
INSULATION CRIMP

PLUG GAGE DIMENSIONS APPLY WHEN TOOL IS BOTTOMED BUT NOT UNDER PRESSURE.

ITEM NO.	NAME	NUMBER	REMARKS
9	SADDLE	307275-1	
8	SCREW (10-32 UNF-3A x .470 LONG)	2-59577-9	
7	SCREW-SPECIAL	59781-6	
6	ANVIL-INSULATION	1-59615-7	
5	ANVIL	59623-6	
4	RING-RETAINING	1-21046-3	
3	INDENTER	59779-2	
2	INDENTER-INSULATION	307285-1	
1	SCREW-S.SPECIAL	59781-2	

SUPERSEDED BY IS-2423

[redacted]

REQUIRED PER ASSEMBLY

©1969 BY AMP INCORPORATED ALL RIGHTS RESERVED
AMP PRODUCTS COVERED BY PATENTS AND/OR PATENTS PENDING

CUSTOMER COPY
REFERENCE ONLY

DR E. Shenfield 11-21-69
DES
CHK
APP 11-26-69

MATERIAL AND FINISH

AMP INCORPORATED HARRISBURG PA

USED ON 69375

WIRE - RANGE - INSULATION 22-16

TYPE CONFINED CRIMP PIDG

TOLERANCE EXCEPT AS NOTED ± .015 ± .1° 0

SCALE 4-1

SPEC MC NO. 69872 REV. B1

NAME DIE ASSEMBLY MOD B

69872

DESCRIPTION

REVISED	DATE
SUPERSEDED BY IS-2423	10-31-69

Downloaded from Elcodis.com electronic components distributor