PLUG GAGE DIMENSIONS APPLY WHEN TOOL IS BOTTOMED BUT NOT UNDER PRESSURE.

NUMBER 69874







ENLARGED VIEW OF CRIMPS

"G" DIM AT POS #1		"C" DIM.	
GO	NO GO	GO	NO GO
.064	.084	.169	.175



SUGGESTED PLUG GAGE FOR "C" DIM. BARREL CRIMP



SUGGESTED PLUG GAGE FOR "G" DIM. INSULATION CRIMP

SUPERSEDED BY 15-2423

ITEM NO.	NUMBER	NAME	REMARKS
9	1 307275-2	SADDLE	
8	1 2-333777-8	SCREW (10-32 UNF-3A x .562 LONG)	
7	1 59781-5	SCREW-SPECIAL	
6	1 1-59613-2	ANVIL-INSULATION	
5	1 59623-4	ANVIL	
4	2 1-21048-3	PINS-RETAINING	
3	1 59779-1	INDENTER	
2	1 307276-1	INDENTER-INSULATION	
1	1 59781-1	SCREW-SPECIAL	

REQUIRED PER ASSEMBLY

©1969 BY AMP INCORPORATED. ALL RIGHTS RESERVED.
AMP PRODUCTS COVERED BY PATENTS AND/OR PATENTS PENDING.

CUSTOMER COPY REFERENCE ONLY

DR E. Swinford 11-24-69
CHK R.J. Swigart 12-1-69
QC
APP R.J. Swigart 12-1-69

MATERIAL AND FINISH

AMP INCORPORATED HARRISBURG, PENNA.

USED ON 69875

WIRE - RANGE - INSULATION 12-10 | PVC INSUL DIAMOND GRIP CONFINED - CRESCENT

TOLERANCE EXCEPT AS NOTED ± .015 | SCALE 4-1 | SIZE C | NO. 69874 | REV. B1

NAME DIE ASSEMBLY MOD B

REVISION RECORD			
A	SUPED BY 15-2423	6-2	7-28
B	REVISED	12-1	11-24

DESCRIPTION

Downloaded from Elcodis.com electronic components distributor