



THE CRIMP DIMS APPLY ONLY TO THE ABOVE COMBINATIONS.

METHOD OF GAGING CRIMP DIMENSIONS.

**SUPERSEDED BY 1.5.2496**

2	-	1-21046-3	RETAINING RING	13
1	B	306205-3	INDENTER-INSULATION	12
1	A	5305932-5	SPACER	11
1	B	1-306542-5	INDENTER-BRAID	10
1	A	5305932-4	SPACER	9
1	B	306207-2	BARREL-INSERT-LOWER	8
1	B	306208-2	BARREL-INSERT-UPPER	7
1	A	5305932-3	SPACER-SPECIAL	6
1	B	1-306541-5	ANVIL-BRAID	5
1	A	1-306113-3	EJECTOR	4
1	B	306206-3	ANVIL-INSULATION	3
2	A	306105-7	SCREW-SPECIAL	2
				1

QTY	NUMBER	NAME	REMARKS	REV NO
		© 1967 BY AMP INCORPORATED. ALL RIGHTS RESERVED. AMP PRODUCTS COVERED BY PATENTS AND/OR PATENTS PENDING.		
<b>CUSTOMER COPY REFERENCE ONLY</b>				
DR	MATERIAL AND FINISH		AMP INCORPORATED HARRISBURG PENNA.	
CHK	C 7/12/67	11	CLAS 11	
DE	1601309	RG-137	TYPE BNC-COAX.	
APP	1601309	WIRE - RANGE - INSULATION	SCALE	LOC NO
		AS NOTED	4-1	M B 69408
		TOLERANCE EXCEPT ± .015 ± 1°		REV NO
LTR REVISION RECORD		DR	CHK	DATE
DESCRIPTION				
DIE ASS'Y				

DIMENSIONS IN INCHES DO NOT SCALE PRINT.

PRINTED IN U.S.A.

AMP 1967 REV 7/68 R