

STEINEL®

STEINEL®



STEINEL · 9051 Lyndale Avenue South · Bloomington · MN 55420  
Telephone 800-852-4343 · Fax 952-888-5132 · www.steinell.net · sales@steinell.net

**HB 1750**  
**Professional Heat Blower Series**

The HB 1750 is the most ergonomically advanced high output blower in its class.

21st Century technology enables STEINEL to achieve maximum airflow from a lightweight, ultra quiet tool. Superior design, materials and workmanship ensure the quality and reliability the STEINEL name guarantees.

For world-class performance...Come Into the Blue.

**Introducing STEINEL Heat Blowers**

**STEINEL Heat Blowers**

HB 1750



Shrink wrap, packaging ...



Dry paint, wall emulsion, filler etc.



Fully adjustable quick-lock stand conveniently stores temperature keys. Tool removes easily for hand-held operation.

**HB 1750**

**High Output**

- Powerful turbine blower with air delivery rate up to 23 CFM
- Color coded keys for the right temperature every time
- Maintenance free factory sealed motor

**Superior Ergonomics**

- Lightweight, well balanced design
- Soft grip handle with convenient slide switch (Off / Cool / Hot)
- Ultra quiet operation

**Convenient Operation**


- Plug-in heating element takes only seconds to change
- Quick-lock stand is fully adjustable and stores keys
- Available accessories enhance versatility

**STEINEL Heat Blowers**

HB 1750



Self-cooling aluminum output tube with mesh guard for safety



Long life heating element with plug-in feature is quick and easy to change



Baffle adjusts air and temperature within range



Plug-in keys are easily interchangeable



**Color coded keys each lock in a specific temperature range**

Color Key	Model	Temperature Range
	HB1750 R	1000 °F - 1200 °F
	HB1750 O	750 °F - 1000 °F
	HB1750 Y	500 °F - 750 °F
	HB1750 G	300 °F - 500 °F
	HB1750 B	200 °F - 300 °F
	HB1750	200 °F - 1200 °F



Slide switch with cool air stage for rapid cool down

Superior ergonomics and soft-grip handle for fatigue-free operation

Double insulated for safe use with all outlets

Made in E.U. ISO 9001:2000

**Specifications**

Item No. 34750	Model HB 1750 (Includes all 5 keys)
34751	HB 1750 B Blower w/ Blue key
34752	HB 1750 G Blower w/ Gray key
34753	HB 1750 Y Blower w/ Yellow key
34754	HB 1750 O Blower w/ Orange key
34755	HB 1750 R Blower w/ Red key
Dimensions (h x w x d)	9 1/2" x 5" x 9 1/2"
Weight	2.4 lbs
Voltage	120 VAC / 60 Hz
Output	1750 W
Temperature	200 °F - 1200 °F (all five keys)
Airflow rate	Up to 23 CFM, adjustable with baffle
Power cord	Industrial grade rubber, length: 6 ft.



**Accessories**



<b>Item No. 07695</b>	<b>Item No. 07725</b>	<b>Item No. 07705</b>	<b>Item No. 07715</b>
<b>1/4" / 7mm Reducer</b>	<b>8" / 200mm Spreader</b>	<b>Large Reflector</b>	<b>Small Reflector</b>
For pinpoint heat	For films and packaging	For shrink tubing up to 50mm diameter	For shrink tubing up to 20 mm diameter