

Isolating Line Transformer

- ~ Provides circuit isolation
- ~ Electrostatic shield between primary & secondary
- ~ Hi-pot tested to 2 KV RMS
- ~ Circuit breaker in primary
- ~ Standard 3-wire, grounded plug & receptacle
- ~ Input (primary) connected to 5 foot long cord & standard North American plug (NEMA 5-15P)
- ~ Output (secondary) connected to 1 foot long 3-wire, standard North American grounded receptacle (NEMA 5-15R)
- ~ North American Mark of Safety: cUL & UL listed



115VAC to 115VAC Isolation Transformer (50/60 Hz.)



Part No.	Capacity VA	Dimensions (Inches)			Mounting Hole Centers (Inches)		Shipping Weight
		W	D	H	W	D	
171A	100	3.80	5.06	4.68	3.00	3.38	6.5 lbs
171B	200	3.80	5.56	4.68	3.00	3.88	8.0 lbs
171C	300	3.80	6.06	4.68	3.00	4.38	11.0 lbs
171E	500	3.80	7.06	4.68	3.00	5.38	14.0 lbs
171F	750	4.40	8.70	5.39	3.50	6.78	30.0 lbs
171G	1000	5.28	7.75	6.38	4.25	4.38	34.5 lbs



- ~ Provides circuit isolation & steps down primary voltage
- ~ Electrostatic shield between primary & secondary
- ~ Hi-pot tested to 2 KV RMS
- ~ Circuit breaker in primary
- ~ Standard 3-wire, grounded plug & receptacle
- ~ Input (primary) connected to 5 foot long cord & European (Schuko) grounded plug
- ~ Output (secondary) connected to 1 foot long 3-wire, standard North American grounded receptacle (NEMA 5-15R)
- ~ North American Mark of Safety: cUL & UL listed



230VAC to 115VAC Step Down Transformer (50/60 Hz.)



Part No.	Capacity VA	Dimensions (Inches)			Mounting Hole Centers (Inches)		Shipping Weight
		W	D	H	W	D	
172A	100	3.80	5.06	4.68	3.00	3.38	6.5 lbs
172B	200	3.80	5.56	4.68	3.00	3.88	8.5 lbs
172D	550	3.80	7.06	4.68	3.00	5.38	18.5 lbs
172E	750	4.40	8.70	5.39	3.50	6.78	30.0 lbs
172F	1000	5.28	7.75	6.38	4.25	4.38	34.5 lbs

