

# LAMINATED TRANSFORMERS

## Type EI42 / 14.8 - 5VA









**AGENCY APPROVALS** 

1. UL 506, File E113449  


3. EN61558  

Primary (V)	Secondary (V / mA)	No-Load Voltage (V)	Schematic No.	Part Number	Agency Approvals
230	6 / 834	8.10	1	<b>042-5381.0</b>	1/3*
230	9 / 556	12.00	1	<b>042-5382.0</b>	1/3*
230	12 / 417	15.50	1	<b>042-5383.0</b>	1/3*
230	15 / 334	19.20	1	<b>042-5384.0</b>	1/3*
230	18 / 278	23.20	1	<b>042-5385.0</b>	1/3*
230	24 / 208	30.50	1	<b>042-5386.0</b>	1/3*
230	2x6 / 417	2x7.80	2	<b>042-5387.0</b>	1/3*
230	2x9 / 278	2x11.60	2	<b>042-5388.0</b>	1/3*
230	2x12 / 208	2x15.20	2	<b>042-5389.0</b>	1/3*
230	2x15 / 167	2x19.40	2	<b>042-5390.0</b>	1/3*

-  Frequency 50/60Hz
-  Potted under vacuum
-  Split-bobbin
-  Temperature class ta 70°C/B
-  Weight: 0.2kg
-  Packaging unit: 15 pieces (tray)

\*NOTE: When checking the approval status of this product with VDE, add the prefix "BV" and the suffix "G" to the orderable Part Number (these letters will also be found on the part label). **The prefix and suffix are not part of the orderable Part Number.**

### Mechanical



### Schematics

