


CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes

more than you expect




\* DIMENSION MAY BE EXCEEDED WITH SOLDER ONLY



**ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:**

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	1-2 @20°C	0.200 ohms ±10%
D.C. RESISTANCE	3-4 @20°C	0.065 ohms ±10%
D.C. RESISTANCE	5-7 tie(5+6, 7+8), @20°C	0.074 ohms ±10%
INDUCTANCE	3-4 10kHz, 100mVAC, Ls	25uH ±10%
SATURATION CURRENT	3-4 20% rolloff from initial	2.0A
LEAKAGE INDUCTANCE	3-4 tie(1+2, 5+6+7+8), 100kHz, 100mVAC, Ls	185nH typ., 300nH max.
DIELECTRIC	3-5 tie(2+4), 1875VAC, 1 second	1500VAC, 1 minute
DIELECTRIC	3-6 tie(2+4), 1875VAC, 1 second	1500VAC, 1 minute
DIELECTRIC	2-3 500VAC, 1 second	400VAC, 1 minute
URNS RATIO	(3-4):(5-7)	1:1, ±1%
URNS RATIO	(3-4):(6-8)	1:1, ±1%
URNS RATIO	(3-4):(2-1)	3:1, ±1%



GENERAL SPECIFICATIONS:  
OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

REV.	DATE	Packaging Specifications Method: Tape & Reel PKG-0523 www.we-online.com/midcom		Tolerances unless otherwise specified: Angles: ±1° Fractions: ±1/64 Decimals: ±.005 [.13] Footprint: ±.005 [.13]	DRAWING TITLE <b>TRANSFORMER</b>	PART NO. <b>750370058</b>
6B	10/10			This drawing is dual dimensioned. Dimensions in brackets are in millimeters.	eISos p/n: 750370058	SPECIFICATION SHEET 1 OF 1
6A	1/09	SEE REVISION SHEET FOR REVISION LEVEL				

