





USB A Type Male
Plastic: White

1,800MM±30MM

USB A Type Female
Plastic: White

P1



P2

Material:

- Cable: UL2725 [28AWG(7/0.127)*1PR+24AWG(7/0.203)*2C +AL-FOIL/MYLAR+DRAIN WIRE(7/0.127)+65% BRAID]TIN
 - OD 4.7MM±0.15MM
 - PVC Jacket
 - Color Black
 - P1 Connector: USB A Type Male
 - Gold Plated 30µ" Contact
 - Nickel Plated Shell
 - P2 Connector: USB A Type Female
 - Gold Plated 30µ" Contact
 - Nickel Plated Shell
 - Hood: Molded Type, PVC 45P, Color Black
 - Tooling Cavity indication for inspection
- Electrical:**
- 100% Open, Short & Mis Wire Test
 - Contact Resistance 3Ω Max.
 - Insulation Resistance 20MΩ Max.

PIN OUT

	P1		P2	
RED	1	_____	1	VCC
WHITE	2	_____	2	-DATA
GREEN	3	_____	3	+DATA
BLACK	4	_____	4	GROUND
SHELL		_____ BRAID _____		SHELL

RoHS
Compliant

ITEM NO.

AK669/2-18-BLACK-R

TITLE

Hi-Speed USB 2.0 Extension cable, 1.8 Meters,
Black, USB A Male <=> USB A Female

ASSMANN
Electronics, Inc.

1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283
Toll Free: 1-877-277-6266 • Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
©Copyright 2010 by Assmann Electronic Components
All International Rights Reserved