
Data Sheet

Chip Monolithic Ceramic Capacitors Safety Standard Certified Type GF (IEC60384-14 Class Y2, X1/Y2) GA342D1XGF330JY02L (1808, SL, 33pF, AC250V(r.m.s.))

• For your new designs, alternative parts should be used. These parts should be used only for existing design. Please consult with us for details.

RoHS regulation conformity parts



(in mm)

Dimensions

| Length L | 4.5mm±0.3mm |
|--------------------|-------------|
| Width W | 2.0mm±0.2mm |
| Thickness T | 2.0mm±0.2mm |
| Electrode e | 0.3mm min. |
| Electrode g (min.) | 2.5mm |

Rated Value

| | Murata PN Code | Spec | |
|-------------------|----------------|---------------------------------|--|
| Temperature Char. | 1X | SL (JIS), +350 to -1000ppm/deg. | |
| Capacitance | 330 | 33pF | |
| Capacitance Tol. | J | ±5% | |
| Rated Voltage | GF | AC250V(r.m.s.) | |

Packaging

| Code | Packaging | Minimum Quantity | |
|------|---------------------|------------------|--|
| L | 180mm Embossed Tape | 2000 | |

Specifications

Please refer to 'Safety Standard Certified Type GC/GD/GF/GB Specifications and Test Methods' PDF file.

Standard Certification

| | Standard | | Status of Certification | | Rated |
|-------|--------------|--------|-------------------------|------------------------------|----------|
| | No. | Class | Size : 4.5×2.0mm | Size : 5.7×2.8mm and over | Voltage |
| UL | UL1414 | X1, Y2 | — | 0 | |
| UL | UL 60950-1 | - | 0 | — | AC250V |
| VDE | IEC 60384-14 | X1, Y2 | _ | 0 | (r.m.s.) |
| SEMKO | EN 60384-14 | Y2 | 0 | 0 | |

Applications

| Size | Switching power supplies | Communication network devices such as a modem | |
|--------------------|--------------------------|---|--|
| 4.5×2.0mm | — | 0 | |
| 5.7×2.8mm and over | O | O | |

• This data sheet is applied to SAFETY STANDARD CERTIFIED CHIP MONOLITHIC CERAMIC CAPACITOR Type GF for your design.

<Notice>

Solderability of Tin plating termination chip might be deteriorated when low temperature soldering profile where peak solder temperature is below the Tin
melting point is used. Please confirm the solderability of Tin plating termination chip before use.

• Plese refer to 'Caution' and 'Notice' for the other details.

The RoHS compliance means that we judge from EU Directive 2002/95/EC the products do not contain lead, cadmium, mercury, hexavalent chromium, PBB and PBDE, except exemptions stated in EU Directive 2002/95/EC annex and impurities existing in natural world.
This statement does not insure the compliance of any of the listed parts with any laws or legal imperatives developed by any EU members

individually with regards to the RoHS Directive.

A Note:

1. This datasheet is downloaded from the website of Murata Manufacturing co., ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.

