## Data Sheet **Chip Monolithic Ceramic Capacitors** Medium Voltage High Capacitance for General Use GRM55DR72E474KW01L (2220, X7R, 0.47µF, DC250V) RoHS regulation conformity parts g When using the following voltage-waveform in applications such as LED Lighting, after a AC bridge rectifier circuit(50/60Hz), additional caution is necessary. Please contact us when selecting capacitors for use in LED Lighting applications. Example of Voltage-waveform: (in mm) Dimensions Packaging Length L 5.7mm±0.4mm Code Packaging Minimum Quantity Width W 5.0mm±0.4mm 180mm Embossed Tape 1000 L Thickness T 2.0mm+0/-0.3mm Specifications Electrode e 0.3mm min. Electrode g (min.) 3.2mm Please refer to 'Medium Voltage High Capacitance for General Use Specifications and Test Methods' Rated Value PDF file. Murata PN Code Spec Temperature Char. X7R (EIA), ±15% R7 Capacitance 474 0.47µF Capacitance Tol. κ ±10% **Rated Voltage** 2E DC250V • This data sheet is applied for CHIP MONOLITHIC CERAMIC CAPACITOR used for General Electronics equipment for your design. <Notice> • Solderability of Tin plating termination chip might be deteriorated when low temperature soldering profile where peak solder temperature is below the Tin melting point is used. Please confirm the solderability of Tin plating termination chip before use. Plese refer to 'Caution' and 'Notice' for the other details. • The RoHS compliance means that we judge from EU Directive 2002/95/EC the products do not contain lead, cadmium, mercury, hexavalent chromium, PBB and PBDE, except exemptions stated in EU Directive 2002/95/EC annex and impurities existing in natural world. • This statement does not insure the compliance of any of the listed parts with any laws or legal imperatives developed by any EU members individually with regards to the RoHS Directive. A Note: 1. This datasheet is downloaded from the website of Murata Manufacturing co., Itd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.

