

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 Fax: (818) 701-4939

### **Features**

- Lead Free Finish/Rohs Compliant (Note1) ("P"Suffix designates Compliant. See ordering information)
- Glass Passivated Junction
- Excellent Clamping Capability
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- UL Recognized File # E331408

### **Mechanical Data**

• Weight : 0.4g

### **Maximum Ratings**


	Symbol	Value	Units
Peak Pulse Power Dissipation	P <sub>PPM</sub>	500(min)	Watts
with a 10/1000 µ s			
Waveform(Note 1)			
Steady State Power Dissipation			
@ T <sub>L</sub> =75 <sup>°</sup> C with lead lengths or	P <sub>M(AV)</sub>	3	Watts
0.375"(9.5mm)			
Peak Pulse Power Surge		See	
Current with a 10/1000 $\mu$ s	I <sub>PPM</sub>	Table1	Amps
Waveform(Note 2. FIG.3)		TableT	
Junction Temperature	ΤJ	-55 to 175	°C
Storage Temperature Range	T <sub>STG</sub>	-55 to 175	°C

NOTE:1) High Temperature Solder Exemptions Applied, see EU Directive Annex 7.

2) Non-repetitive current pulse, per Fig.3 and derated above TA=25 $^\circ\!\!\mathbb{C}$  , per Fig.2

# SAC5.0 THRU SAC50

## 500W Low Capacitance Transient Voltage Suppressor



DIMENSIONS					
DIM	INCHES		ММ		NOTE
	MIN	MAX	MIN	MAX	NOTE
А	0.230	0.300	5.80	7.60	
В	0.104	0.140	2.60	3.60	
С	0.026	0.034	0.71	0.86	
D	1.000		25.40		

SAC5.0 THRU SAC50



**Micro Commercial Components** 

### **ELECTRICAL CHARACTERISTICS @25°C**

1								
	STAND-OFF	MINIMUM	MAXIMUM	MAXIMUM	MAXIMUM	MAXIMUM	WORKING	PEAK
	VOLTAGE	BREAKDOWN	REVERSE	CLAMPING	PEAK	JUNCTION	INVERSE	INVERSE
MCC	(NOTE 1)	VOLTAGE	LEAKAGE	VOLTAGE	PULSE	CAPACITAN	BLOCKING	BLOCKING
PART	V <sub>WM</sub>	AT I⊤=1.0Ma	AT V <sub>WM</sub>	AT I <sub>PP</sub> =5.0A	CURRENT	CE AT 0	VOLTAGE	VOLTAGE
NUMBER	• VVIVI	V <sub>(BR)</sub>	IR	V <sub>C</sub>	PER FIG.3	VOLTS	V <sub>WIB</sub>	VPIB
NOWBER		V (BR)		٧C	IPP	VOLIO	A MIR	V PIB
	V	V	μA	V	Amps	pF	V	V
SAC5.0	5.0	7.60	300	10.0	44.0	50	75	100
SAC6.0	6.0	7.90	300	11.2	41.0	50	75	100
SAC7.0	7.0	8.33	300	12.6	38.0	50	75	100
SAC8.0	8.0	8.89	100	13.4	36.0	50	75	100
SAC8.5	8.5	9.44	50	14.0	34.0	50	75	100
SAC10	10.0	11.10	5	16.3	29.0	50	75	100
SAC12	12.0	13.30	5	19.0	25.0	50	75	100
SAC15	15.0	16.70	5	23.6	20.0	50	75	100
SAC18	18.0	20.00	5	28.8	15.0	50	75	100
SAC22	22.0	24.40	5	35.4	14.0	50	75	100
SAC26	26.0	28.90	5	42.3	11.1	50	75	100
SAC30	30.0	33.30	5	48.6	10.0	50	75	100
SAC36	36.0	40.00	5	60.0	8.6	50	75	100
SAC45	45.0	50.00	5	77.0	6.8	50	150	200
SAC50	50.0	55.50	5	88.0	5.8	50	150	200

NOTE:

1) Non-repetitive current pulse, per Fig.3 and derated above TA=25 $^\circ\!\mathbb{C},$  per Fig.2


**Revision:** A Downloaded from <u>Elcodis.com</u> electronic components distributor


www.mccsemi.com


## SAC5.0 THRU SAC50




Ratings and Characteristic Curves(TA=25°C unless otherwise noted)









Application Note: Device must be used with two units in parallel,opposite in polarity as shown in circuit for AC signal line protection.

## www.mccsemi.com



### **Ordering Information :**

Device	Device Packing	
Part Number-TP	Tape&Reel: 4Kpcs/Reel	
Part Number-AP	Ammo Packing: 3Kpcs/Ammo Box	
Part Number-BP	Bulk: 25Kpcs/Carton	

#### **\*\*\*IMPORTANT NOTICE\*\*\***

*Micro Commercial Components Corp.* reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

# www.mccsemi.com