



- NOTES:
1. THIS SPECIFICATION COVERS THE REQUIREMENT FOR A DUAL 92/184 ROW EDGECARD CONNECTOR
  2. INSULATOR MATERIAL: POLYPHENYLENE SULFIDE. (BLACK)
  3. CONTACT MATERIAL: PHOSPHOR BRONZE.
  4. PLATING: .00001" GOLD ON CONTACT SURFACE  
.00001" TIN/LEAD ON TERMINAL  
.00005" NICKEL UNDERPLATE
  5. TEMPERATURE: -65°C TO 125°C
  6. UL FLAMMABILITY RATING: 94V-0
  7. VOLTAGE RATING: 125 VDC MINIMUM AT SEA LEVEL.
  8. CURRENT RATING: 1 AMP
  9. VOLTAGE DROP: 30 MILLI VOLT AT RATED CURRENT
  10. INSULATION RESISTANCE: 1000 MEGA OHM
  11. CONNECTOR IDENTIFICATION: THE PART SHALL BE MARKED WITH A PART NUMBER AND DATE CODE.
  12. BOARD THICKNESS ACCOMMODATED: .062 [1.57]
  13. BOARD INSERTION FORCE: 6 OUNCE AVERAGE PER CONTACT PAIR USING .062 [1.57] PCB
  14. BOARD WITHDRAWAL FORCE: 1 OUNCE MINIMUM PER CONTACT PAIR USING .062 [1.57] PCB
  15. TOLERANCE: ±.010" UNLESS OTHERWISE NOTED.
  16. MODIFICATION: MOLDED KEY BETWEEN POSITIONS 49 AND 52, 62 AND 65

COMPUTER GENERATED DOCUMENT DO NOT CHANGE MANUALLY

PROPRIETARY AND CONFIDENTIAL  
THIS DRAWING AND DESIGN IS THE PROPERTY OF SULLINS ELECTRONICS. IT MAY NOT BE USED FOR ANY PURPOSE OTHER THAN BY THE OWNER. SULLINS ELECTRONICS DOES NOT AUTHORIZE THE REPRODUCTION OR CONVEYANCE OF ANY INFORMATION CONTAINED HEREIN.

A	120	ORIGINAL RELEASE	01/09/04	AN	AJT
REV.	ECO NO.	DESCRIPTION	DATE	BY	APPVD
		UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONS & .010 DECIMALS & .005 ANGULAR ± 1° HOLE POSITION ± .010 HOLE DIA ± .005 HOLE DRILL ± .005 HOLE LOCATION ± .010	DRAWN 01/09/04 CHECKED 01/09/04	ARA AJT	
NEXT ASSY		USED ON	FINISH	N/A	
APPLICATION		DO NOT SCALE DRAWING			

SULLINS ELECTRONICS  
 PART NO./DESCRIPTION:  
 RZB92DHAS-S250  
 SIZE C DWG. NO. 10126 REV A  
 SCALE: 2:1 SHEET 1 OF 1