



4pos



Directive 2002/95/EC
„RoHS“
Compliant

Technical specification:

Rated voltage: IEC 60664-1	4pos 250 V
Current rating: IEC 60512-3	9A at 40°C
Insulation resistance: IEC 60512-2	>=10 GΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: IEC 60529	IP 67, in mated condition
Temperature range: IEC 60664-1	-40°C ... +85°C
Mating cycles: IEC 60512-9a	<=100
Wire cross section:	AWG16 / max. 1,5mm ²
Contact termination:	Screw connection
Materials:	
Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	TPU, UL 94
Cable sealing:	Elastomere
Coupling nut:	CuZn, nickel plated
Housing:	PA6 GF, UL 94

Part no:	Description:	Cable sealing:
41-00002	SAL - 7/8 - RKC4 - S	For external diameter 6-8mm, 8-10mm, 10-12mm

DO NOT ALTER CAD DRAWING BY HAND	Status: 05.05.08 Mkf	dim. in mm	title: Female connector 7/8", 4pos field attachable, axial, with screw connection										
	tolerance: ISO 2768-m												
	THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH	<table border="1"> <tr> <td></td> <td>date</td> <td>name</td> </tr> <tr> <td>drawn</td> <td>11.10.07</td> <td>Burschik</td> </tr> <tr> <td>appd.</td> <td>01.11.07</td> <td>Schmidt</td> </tr> </table>		date	name	drawn	11.10.07	Burschik	appd.	01.11.07	Schmidt	dwg no: Inventor 10	
			date	name									
drawn	11.10.07	Burschik											
appd.	01.11.07	Schmidt											
		41K1A326											
			part no:										