



- CONTACT CAVITIES IDENTIFIED BY CHARACTERS ON FRONT AND REAR FACES OF CONNECTOR.
 - #6 FASTENER RECOMMENDED FOR MOUNTING.
- △ CONTACT BODY: .000100 MIN TIN-LEAD OVER .000050 MIN NICKEL.
 CONTACT POST: .000100 MIN TIN-LEAD OVER .000100 MIN COPPER.
 - △ CONTACT BODY: .000030 MIN GOLD FOR A LENGTH OF .250 MIN FROM MATING END, WITH REMAINDER TO BE GOLD FLASH, BOTH OVER .000050 MIN NICKEL.
 CONTACT POST: .000100 MIN TIN-LEAD OVER .000100 MIN COPPER.
 - △ PC BOARD HOLE PATTERN IS DEFINED RELATIVE TO CONNECTOR C.L.
 - △ FREE HANGING RECEPTACLE.
 - △ CONTACT BODY: .000100 MIN TIN OVER .000050 MIN NICKEL.
 CONTACT POST: .000100 MIN TIN OVER .000100 MIN COPPER.
 - △ CONTACT BODY: .000030 MIN GOLD FOR A LENGTH OF .250 MIN FROM MATING END, WITH REMAINDER TO BE GOLD FLASH, BOTH OVER .000050 MIN NICKEL.
 CONTACT POST: .000100 MIN TIN OVER .000100 MIN COPPER.

PRELIMINARY	△	1-796387-2
	△	1-796387-1
	△	796387-3
	△	796387-2
	△	796387-1
NOTES	CONTACT FINISH	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DATE	4-2-90	REVISED	4-2-90
DESIGNED BY	REVISIONS	DATE	DESCRIPTION	BY	CHK
HOLES	1	4-2-90	REVISED PER 0230-0100-05	SS	HW
DRAWN BY	2	4-2-90			
CHECKED BY	3	4-2-90			
APPROVED BY	4	4-2-90			
DATE	4-2-90	SIZE	A	00778	00778
CUSTOMER DRAWING		DATE	2-1	REV	1