

Models 6855
XLR (M) 5-Pin Rectangular Flanged Panel Mount

Model 6855 XLR (M) 5-pin rectangular flanged mount

Protect contacts and absorb vibrations in your audio applications.

Features

- 5-pin XLR panel mount with sturdy all metal one piece design.
- Solder cup terminations.
- Front mountable.

Materials

- Housing is made of die-cast zinc alloy with tarnish resistant nickel plating.
- Contacts are bronze with tin finish.
- Ground tab is made of steel.

Ordering Information

Model: 6855.

Specifications

| | |
|---------------------|------------------------------------|
| Number of contacts | 5 |
| Contact resistance | < 5 m Ω |
| Dielectric strength | 1500 V dc |
| Wire size (AWG) | 18 AWG (1.0 mm ²) max. |

USA: Sales: 800-490-2361 Technical Support: 800-241-2060 Fax: 888-403-3360

Europe: 31-(0) 40 2675 150 **International:** 425-446-5500

e-mail: technicalsupport@pomonatest.com

Where to Buy: www.pomonaelectronics.com

All dimensions are in inches. Tolerances (except noted): .xx = $\pm .02$ " (.51 mm), .xxx = $\pm .005$ " (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.