



A : MATERIAL  
 1. PIN : BRONZE  
 2. INSULATION : P.C.(or NYLON)  
 3. METAL SHELL : BRONZE, NICKEL PLATED.  
 4. SHELL : A.B.S.  
 5. COVER : P.V.C.

B : ELECTRICAL  
 RATING : 100V AC / 1 A MAX.  
 INSULATION RESISTANCE : 50M OHM / 500V DC  
 DIELECTRIC : 500V AC / 1 MINUTE  
 CONTACT RESISTANCE : 30M OHM MAX.  
 C : APPLICABLE WIRE SIZE :  
 AWG #24 ~ AWG #28

ARRANGEMENT OF CONTACTS FRONT VIEW	NO. OF CONTACTS
	3
	4
	5
	6
	7
	8
	9

SINGATRON ENT. CO., LTD. (U.S.A.)

REVISION LIST		TOLERANCE :		SCALE		TITLE :	
REV	DESCRIPTION	DATE	.XX=	.XXX=	NONE		DWG. NO.
A	INITIAL RELEASE OF DWG	FEB 02,96					
B	ADD PIN DIM.	SEP 16,96					
APPROVED BY							
DRAWN BY							
CHECK BY							
UNIT						MM	
P/N: 62000-XP-S							
SHEET 1 OF 1							
							REV. B