





REV	DATE	DESCRIPTION	BY	CHK	APP
00					
01		REVISED PER EDD-11-004587			



RECOMMENDED HOLE LAYOUT

- △ .00076[.000030] GOLD IN THE CONTACT AREA, .00254[.000100] MATTE TIN-LEAD ON REMAINDER OF CONTACT, ALL OVER .00127[.000050] NICKEL.
- △ POINT OF MEASUREMENT FOR PLATING THICKNESS.
- △ THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND THE HOUSING.
- △ ON ASSEMBLIES WITH FOUR OR MORE POSITIONS, TWO POLARIZATION SLOTS; ON ASSEMBLIES WITH TWO OR THREE POSITIONS, ONE POLARIZATION SLOT.
- △ .00076[.000030] GOLD IN THE CONTACT AREA, .00254[.000100] MATTE TIN ON REMAINDER OF CONTACT, ALL OVER .00127[.000050] NICKEL.
- △ HIGH TEMPERATURE CONFIGURATION
- △ STANDOFFS NOT PRESENT ON UNDERSIDE OF ASSEMBLY
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

REMARKS	PLATING	C	B	A	NO. OF POSN	PART NO.
		64.01 [2.520]	66.04 [2.600]	24	25	2-103735-4
△ OBSOLETE	△	61.47 [2.420]	63.50 [2.500]	23	24	2-103735-3
△ OBSOLETE	△	58.93 [2.320]	60.96 [2.400]	22	23	2-103735-2
△ OBSOLETE	△	56.39 [2.220]	58.42 [2.300]	21	22	2-103735-1
△ OBSOLETE	△	53.85 [2.120]	55.88 [2.200]	20	21	2-103735-0
	△	51.31 [2.020]	53.34 [2.100]	19	20	1-103735-9
△ OBSOLETE	△	48.77 [1.920]	50.80 [2.000]	18	19	1-103735-8
	△	46.23 [1.820]	48.26 [1.900]	17	18	1-103735-7
	△	43.69 [1.720]	45.72 [1.800]	16	17	1-103735-6
	△	41.15 [1.620]	43.18 [1.700]	15	16	1-103735-5
	△	38.61 [1.520]	40.64 [1.600]	14	15	1-103735-4
	△	36.07 [1.420]	38.10 [1.500]	13	14	1-103735-3
	△	33.53 [1.320]	35.56 [1.400]	12	13	1-103735-2
	△	30.99 [1.220]	33.02 [1.300]	11	12	1-103735-1
	△	28.45 [1.120]	30.48 [1.200]	10	11	1-103735-0
	△	25.91 [1.020]	27.94 [1.100]	9	10	103735-9
	△	23.37 [0.920]	25.40 [1.000]	8	9	103735-8
	△	20.83 [0.820]	22.86 [0.900]	7	8	103735-7
	△	18.29 [0.720]	20.32 [0.800]	6	7	103735-6
	△	15.75 [0.620]	17.78 [0.700]	5	6	103735-5
	△	13.21 [0.520]	15.24 [0.600]	4	5	103735-4
	△	10.67 [0.420]	12.70 [0.500]	3	4	103735-3
	△	8.13 [0.320]	10.16 [0.400]	2	3	103735-2
	△	5.59 [0.220]	7.62 [0.300]	1	2	103735-1

THIS DRAWING IS A CONTROLLED DOCUMENT. THE SHIELD 3-3-81

TE Connectivity

INDUCTIONS: DIMENSIONS UNLESS OTHERWISE SPECIFIED ARE IN MILLIMETERS

FINISHES: 1. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE TO BE HONED TO THE FINISH SPECIFIED. 2. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE TO BE HONED TO THE FINISH SPECIFIED.

DATE: 10/07/99

REVISED PER EDD-11-004587

DATE: 10/07/99

REVISED PER EDD-11-004587

DATE: 10/07/99

REVISED PER EDD-11-004587

THIS DRAWING IS UNPUBLISHED  
 ALL RIGHTS RESERVED

REVISES		DATE	BY	APP
1	SEE SHEET 1	-	-	-

REMARKS	PLATING	C	B	A	NO. OF POSN	PART NO.
△ OBSOLETE	△ △ △	△	64.01 [2.520]	66.04 [2.600]	24 25	7-103735-4
△ OBSOLETE	△ △ △	△	61.47 [2.420]	63.50 [2.500]	23 24	7-103735-3
△ OBSOLETE	△ △ △	△	58.93 [2.320]	60.96 [2.400]	22 23	7-103735-2
△ OBSOLETE	△ △ △	△	56.39 [2.220]	58.42 [2.300]	21 22	7-103735-1
△ OBSOLETE	△ △ △	△	53.85 [2.120]	55.88 [2.200]	20 21	7-103735-0
△ OBSOLETE	△ △ △	△	51.31 [2.020]	53.34 [2.100]	19 20	6-103735-9
△ OBSOLETE	△ △ △	△	48.77 [1.920]	50.80 [2.000]	18 19	6-103735-8
△ OBSOLETE	△ △ △	△	46.23 [1.820]	48.26 [1.900]	17 18	6-103735-7
△ OBSOLETE	△ △ △	△	43.69 [1.720]	45.72 [1.800]	16 17	6-103735-6
△ OBSOLETE	△ △ △	△	41.15 [1.620]	43.18 [1.700]	15 16	6-103735-5
△ OBSOLETE	△ △ △	△	38.61 [1.520]	40.64 [1.600]	14 15	6-103735-4
△ OBSOLETE	△ △ △	△	36.07 [1.420]	38.10 [1.500]	13 14	6-103735-3
△ OBSOLETE	△ △ △	△	33.53 [1.320]	35.56 [1.400]	12 13	6-103735-2
△ OBSOLETE	△ △ △	△	30.99 [1.220]	33.02 [1.300]	11 12	6-103735-1
△ OBSOLETE	△ △ △	△	28.45 [1.120]	30.48 [1.200]	10 11	6-103735-0
△ OBSOLETE	△ △ △	△	25.91 [1.020]	27.94 [1.100]	9 10	5-103735-9
△ OBSOLETE	△ △ △	△	23.37 [.920]	25.40 [1.000]	8 9	5-103735-8
△ OBSOLETE	△ △ △	△	20.83 [.820]	22.86 [.900]	7 8	5-103735-7
△ OBSOLETE	△ △ △	△	18.29 [.720]	20.32 [.800]	6 7	5-103735-6
△ OBSOLETE	△ △ △	△	15.75 [.620]	17.78 [.700]	5 6	5-103735-5
△ OBSOLETE	△ △ △	△	13.21 [.520]	15.24 [.600]	4 5	5-103735-4
△ OBSOLETE	△ △ △	△	10.67 [.420]	12.70 [.500]	3 4	5-103735-3
△ OBSOLETE	△ △ △	△	8.13 [.320]	10.16 [.400]	2 3	5-103735-2
△ OBSOLETE	△ △ △	△	5.59 [.220]	7.62 [.300]	1 2	5-103735-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

TE Connectivity  
 HDR ASSY, VERT, SINGLE ROW  
 2.54(100) & 0.64(.025) SQ POST,  
 WITH FLN & LATCHING, AMPRODOL MTE

DATE: 00779  
 DRAWING NO: G=103735

CUSTOMER DRAWING

DATE: 4.1 SHEET 2 OF 2