

THIS DRAWING IS UNPUBLISHED
 ALL RIGHTS RESERVED

REV	DATE	DESCRIPTION	BY	CHK	APP
00					

- △ COORDINATE DIMENSION APPLIES FROM BASIC LOCATION.
- △ 6 POSITION SIZE DOES NOT HAVE SLOTS FOR SNAP-IN POLARIZER (MILITARY POLARIZATION). 10 AND 14 POSITION SIZES CONTAIN ONLY ONE SLOT FOR SNAP-IN POLARIZER (MILITARY POLARIZATION) LOCATED AS SHOWN.
- △ 6 POSITION SIZE DOES NOT HAVE SLOTS FOR DUAL POLARIZATION. 10 POSITION SIZES CONTAIN ONLY ONE SLOT FOR DUAL POLARIZATION, LOCATED AS SHOWN.
- 4. RECOMMENDED PRINTED CIRCUIT BOARD THICKNESS IS 1.57 [.062].
- △ DISTANCE REQUIRED BY EJECTION LATCHES IN THE OPEN POSITION.
- △ HOUSING & LATCHES: GLASS FILLED NYLON OR POLYESTER, UL 94V-0 RATED, SEE TABLE FOR COLOR. POSTS: PHOS BRONZE OR BRASS.
- △ POSTS: GOLD FLASH OVER PALLADIUM-NICKEL PLATE, 0.76µm[.000030] MIN TOTAL ON THE LOCALIZED PLATE AREA, 2.54µm[.000100] MIN TIN PLATE ON THE SOLDER-TAIL, 1.27µm[.000050] MIN NICKEL UNDERPLATE ON THE ENTIRE POST.
 -OR-
 0.76µm[.000030] MIN GOLD PLATE ON THE LOCALIZED PLATE AREA, 2.54µm[.000100] MIN TIN PLATE ON THE SOLDER-TAIL, 1.27µm[.000050] MIN NICKEL UNDERPLATE ON THE ENTIRE POST.
- △ DATUMS -M- & -N- TO BE ESTABLISHED BY CUSTOMER.
- △ DEVELOPMENT PART NUMBER, REV 1 - NOT RELEASED FOR PRODUCTION.

POST	6	10	14	20	24	30	36	40	44	50	60	64	REVISIONS	
BLUE	2.78 [.110]	5.08 [.200]	22.86 [.900]	16.76 [.660]	26.92 [1.060]	22.86 [.900]	12.70 [.500]						6	3-5499206-4
BLUE		53.34	71.12	65.02	75.18	71.12	60.96						44	3-5499206-3
OBSOLETE BLUE		78.74	96.52	90.42	100.58	96.52	86.36						64	3-5499206-2
BLUE		73.66	91.44	85.34	95.50	91.44	81.28						60	3-5499206-1
BLUE		60.96	78.74	72.64	82.80	78.74	68.58						50	3-5499206-0
BLUE		48.26	66.04	59.94	70.10	66.04	55.88						40	2-5499206-9
BLUE		40.64	58.42	52.32	62.48	58.42	48.26						34	2-5499206-8
OBSOLETE BLUE		35.56	53.34	47.24	57.40	53.34	43.18						30	2-5499206-7
BLUE		30.48	48.26	42.16	52.32	48.26	38.10						26	2-5499206-6
BLUE		22.86	40.64	34.54	44.70	40.64	30.48						20	2-5499206-4
BLUE		17.78	35.56	29.46	39.62	35.56	25.40						16	2-5499206-3
BLUE		15.24	33.02	26.92	37.08	33.02	22.86						14	2-5499206-2
BLUE		10.16	27.94	21.84	32.00	27.94	17.78						10	2-5499206-1
BLACK		78.74	96.52	90.42	100.58	96.52	86.36						64	1-5499206-2
BLACK	4.19 [.165]	73.66	91.44	85.34	95.50	91.44	81.28						60	1-5499206-1
BLACK		60.96	78.74	72.64	82.80	78.74	68.58						50	1-5499206-0
BLACK		48.26	66.04	59.94	70.10	66.04	55.88						40	5499206-9
BLACK		40.64	58.42	52.32	62.48	58.42	48.26						34	5499206-8
BLACK		35.56	53.34	47.24	57.40	53.34	43.18						30	5499206-7
BLACK		30.48	48.26	42.16	52.32	48.26	38.10						26	5499206-6
BLACK		27.94	45.72	39.62	49.78	45.72	35.56						24	5499206-5
BLACK		22.86	40.64	34.54	44.70	40.64	30.48						20	5499206-4
BLACK		17.78	35.56	29.46	39.62	35.56	25.40						16	5499206-3
BLACK		15.24	33.02	26.92	37.08	33.02	22.86						14	5499206-2
BLACK		10.16	27.94	21.84	32.00	27.94	17.78						10	5499206-1
HOUSING AND LATCHES COLOR	G	F	E	D	C	B	A						NO OF POS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. **TE Connectivity**

DESIGNED BY: M. WILMSLEY
 DRAWN BY: M. WILMSLEY
 CHECKED BY: M. WILMSLEY
 APPROVED BY: M. WILMSLEY

DATE: 108-40018
 SIZE: A1
 REV: 2

TE Connectivity
 HEADERS ASSY, UNIVERSAL
 AMP-LATCH

CUSTOMER DRAWING