


- ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
 - TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADERS ARE HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- Δ THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
 Δ POINT OF MEASUREMENT FOR PLATING THICKNESS
 Δ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI



	3.984	3.900	39	40	4-103185-0
Δ	3.884	3.800	38	39	3-103185-9
Δ	3.784	3.700	37	38	3-103185-8
Δ	3.684	3.600	36	37	3-103185-7
Δ	3.584	3.500	35	36	3-103185-6
Δ	3.484	3.400	34	35	3-103185-5
Δ	3.384	3.300	33	34	3-103185-4
Δ	3.284	3.200	32	33	3-103185-3
Δ	3.184	3.100	31	32	3-103185-2
Δ	3.084	3.000	30	31	3-103185-1
Δ	2.984	2.900	29	30	3-103185-0
Δ	2.884	2.800	28	29	2-103185-9
Δ	2.784	2.700	27	28	2-103185-8
Δ	2.684	2.600	26	27	2-103185-7
Δ	2.584	2.500	25	26	2-103185-6
Δ	2.484	2.400	24	25	2-103185-5
Δ	2.384	2.300	23	24	2-103185-4
Δ	2.284	2.200	22	23	2-103185-3
Δ	2.184	2.100	21	22	2-103185-2
Δ	2.084	2.000	20	21	2-103185-1
Δ	1.984	1.900	19	20	2-103185-0
Δ	1.884	1.800	18	19	1-103185-9
Δ	1.784	1.700	17	18	1-103185-8
Δ	1.684	1.600	16	17	1-103185-7
Δ	1.584	1.500	15	16	1-103185-6
Δ	1.484	1.400	14	15	1-103185-5
Δ	1.384	1.300	13	14	1-103185-4
Δ	1.284	1.200	12	13	1-103185-3
Δ	1.184	1.100	11	12	1-103185-2
Δ	1.084	1.000	10	11	1-103185-1
Δ	0.984	0.900	9	10	1-103185-0
Δ	.884	.800	8	9	103185-9
Δ	.784	.700	7	8	103185-8
Δ	.684	.600	6	7	103185-7
Δ	.584	.500	5	6	103185-6
Δ	.484	.400	4	5	103185-5
Δ	.384	.300	3	4	103185-4
Δ	.284	.200	2	3	103185-3
Δ	.184	.100	1	2	103185-2
Δ	.084			1	103185-1
	C	B	A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DESIGNER	DATE	REVISED BY	DATE
APPROVED BY	DATE	REVISED BY	DATE

THIS DRAWING IS A CONTROLLED DOCUMENT. ALL RIGHTS RESERVED.

CUSTOMER DRAWING DATE: 4.1 SHEET: 1 OF 1 REV: G2