



RECOMMENDED PC BOARD MOUNTING DIMENSIONS
 FOR .063 [1.60] THICK PC BOARD AND
 .012 [0.305] STENCIL THICK.

- ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
- TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
- 0.00762 [0.00030] GOLD IN CONTACT AREA, 0.00254-0.00508 [0.000100-0.000200] MATTE TIN-LEAD ON SOLDER TAIL, ALL OVER 0.00127 [0.00050] NICKEL.
- MATERIAL: HOUSING - LCP, COLOR: BLACK, POSTS - PHOSPHOR BRONZE
- 0.00762 [0.00030] GOLD IN CONTACT AREA, 0.00254-0.00508 [0.000100-0.000200] MATTE TIN ON SOLDER TAIL, ALL OVER 0.00127 [0.00050] NICKEL.
- OBsolete PARTS: OBsolete CIS STREAMLINING PER D.RENAUD/D.SINISI

NO	DEF	REV	DESCRIPTION	DATE	BY	APP
AD	00	F2	REVISED PER EDD-11-004587		11MM11	RK HMR

NO	DEF	REV	DESCRIPTION	DATE	BY	APP
101.19	99.06	39	40	9-146281-0		
101.19	99.06	39	40	4-146281-0		
101.19	99.06	39	40	8-146281-9		
101.19	99.06	39	40	8-146281-8		
101.19	99.06	39	40	8-146281-7		
101.19	99.06	39	40	8-146281-6		
101.19	99.06	39	40	8-146281-5		
101.19	99.06	39	40	8-146281-4		
101.19	99.06	39	40	8-146281-3		
101.19	99.06	39	40	8-146281-2		
101.19	99.06	39	40	8-146281-1		
101.19	99.06	39	40	8-146281-0		
101.19	99.06	39	40	7-146281-9		
101.19	99.06	39	40	7-146281-8		
101.19	99.06	39	40	7-146281-7		
101.19	99.06	39	40	7-146281-6		
101.19	99.06	39	40	7-146281-5		
101.19	99.06	39	40	7-146281-4		
101.19	99.06	39	40	7-146281-3		
101.19	99.06	39	40	7-146281-2		
101.19	99.06	39	40	7-146281-1		
101.19	99.06	39	40	7-146281-0		
101.19	99.06	39	40	6-146281-9		
101.19	99.06	39	40	6-146281-8		
101.19	99.06	39	40	6-146281-7		
101.19	99.06	39	40	6-146281-6		
101.19	99.06	39	40	6-146281-5		
101.19	99.06	39	40	6-146281-4		
101.19	99.06	39	40	6-146281-3		
101.19	99.06	39	40	6-146281-2		
101.19	99.06	39	40	6-146281-1		
101.19	99.06	39	40	6-146281-0		
101.19	99.06	39	40	5-146281-9		
101.19	99.06	39	40	5-146281-8		
101.19	99.06	39	40	5-146281-7		
101.19	99.06	39	40	5-146281-6		
101.19	99.06	39	40	5-146281-5		
101.19	99.06	39	40	5-146281-4		
101.19	99.06	39	40	5-146281-3		
101.19	99.06	39	40	5-146281-2		
101.19	99.06	39	40	5-146281-1		
101.19	99.06	39	40	5-146281-0		
101.19	99.06	39	40	4-146281-9		
101.19	99.06	39	40	4-146281-8		
101.19	99.06	39	40	4-146281-7		
101.19	99.06	39	40	4-146281-6		
101.19	99.06	39	40	4-146281-5		
101.19	99.06	39	40	4-146281-4		
101.19	99.06	39	40	4-146281-3		
101.19	99.06	39	40	4-146281-2		
101.19	99.06	39	40	4-146281-1		
101.19	99.06	39	40	4-146281-0		

THIS DRAWING IS A CONTROLLED DOCUMENT.

TE Connectivity

HEADER ASSEMBLY, WOOD II, BREAKAWAY, SINGLE ROW, HIGH TEMPERATURE, VERTICAL W/250 SQ POSTS, 100 EC

DATE: 01/07/79

CUSTOMER DRAWING