



- △ THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
- △ POINT OF MEASUREMENT FOR PLATING THICKNESS.
- 3 ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
- △ BREAKAWAY NOTCH ANGLE CAN BE ORIENTED TO THE RIGHT (AS SHOWN) OR TO THE LEFT
- △ .00015 GOLD IN THE CONTACT AREA.  
.000100-.000200 MATTE TIN-LEAD ON THE SOLDER TAIL.  
.000050 NICKEL ALL OVER.
- △ .000015 GOLD IN THE CONTACT AREA.  
.000100-.000200 MATTE TIN ON THE SOLDER TAIL.  
.000050 NICKEL ALL OVER.
- △ MATERIAL:  
HOUSING- FLAME RETARDANT THERMOPLASTIC, COLOR-BLACK  
POSTS- PHOS BRONZE
- △ HIGH TEMPERATURE CONFIGURATION.
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

REMARKS	PLATING	C	B	A	NO OF POSN	ASSEMBLY PART NUMBER
△ OBSOLETE		3.984	3.900	39	80	9-102975-0
△		3.884	3.800	38	78	8-102975-9
△		3.784	3.700	37	76	8-102975-8
△		3.684	3.600	36	74	8-102975-7
△		3.584	3.500	35	72	8-102975-6
△		3.484	3.400	34	70	8-102975-5
△		3.384	3.300	33	68	8-102975-4
△		3.284	3.200	32	66	8-102975-3
△		3.184	3.100	31	64	8-102975-2
△		3.084	3.000	30	62	8-102975-1
△		2.984	2.900	29	60	8-102975-0
△		2.884	2.800	28	58	7-102975-9
△		2.784	2.700	27	56	7-102975-8
△		2.684	2.600	26	54	7-102975-7
△		2.584	2.500	25	52	7-102975-6
△		2.484	2.400	24	50	7-102975-5
△		2.384	2.300	23	48	7-102975-4
△		2.284	2.200	22	46	7-102975-3
△		2.184	2.100	21	44	7-102975-2
△		2.084	2.000	20	42	7-102975-1
△		1.984	1.900	19	40	7-102975-0
△		1.884	1.800	18	38	6-102975-9
△		1.784	1.700	17	36	6-102975-8
△		1.684	1.600	16	34	6-102975-7
△		1.584	1.500	15	32	6-102975-6
△		1.484	1.400	14	30	6-102975-5
△		1.384	1.300	13	28	6-102975-4
△		1.284	1.200	12	26	6-102975-3
△		1.184	1.100	11	24	6-102975-2
△		1.084	1.000	10	22	6-102975-1
△		.984	.900	9	20	6-102975-0
△		.884	.800	8	18	5-102975-9
△		.784	.700	7	16	5-102975-8
△		.684	.600	6	14	5-102975-7
△		.584	.500	5	12	5-102975-6
△		.484	.400	4	10	5-102975-5
△		.384	.300	3	8	5-102975-4
△		.284	.200	2	6	5-102975-3
△		.184	.100	1	4	5-102975-2
△		.084	---	---	2	5-102975-1

REMARKS	PLATING	C	B	A	NO OF POSN	ASSEMBLY PART NUMBER
△ OBSOLETE		3.984	3.900	39	80	4-102975-0
△		3.884	3.800	38	78	3-102975-9
△		3.784	3.700	37	76	3-102975-8
△		3.684	3.600	36	74	3-102975-7
△		3.584	3.500	35	72	3-102975-6
△		3.484	3.400	34	70	3-102975-5
△		3.384	3.300	33	68	3-102975-4
△		3.284	3.200	32	66	3-102975-3
△		3.184	3.100	31	64	3-102975-2
△		3.084	3.000	30	62	3-102975-1
△		2.984	2.900	29	60	3-102975-0
△		2.884	2.800	28	58	2-102975-9
△		2.784	2.700	27	56	2-102975-8
△		2.684	2.600	26	54	2-102975-7
△		2.584	2.500	25	52	2-102975-6
△		2.484	2.400	24	50	2-102975-5
△		2.384	2.300	23	48	2-102975-4
△		2.284	2.200	22	46	2-102975-3
△		2.184	2.100	21	44	2-102975-2
△		2.084	2.000	20	42	2-102975-1
△		1.984	1.900	19	40	2-102975-0
△		1.884	1.800	18	38	1-102975-9
△		1.784	1.700	17	36	1-102975-8
△		1.684	1.600	16	34	1-102975-7
△		1.584	1.500	15	32	1-102975-6
△		1.484	1.400	14	30	1-102975-5
△		1.384	1.300	13	28	1-102975-4
△		1.284	1.200	12	26	1-102975-3
△		1.184	1.100	11	24	1-102975-2
△		1.084	1.000	10	22	1-102975-1
△		.984	.900	9	20	1-102975-0
△		.884	.800	8	18	102975-9
△		.784	.700	7	16	102975-8
△		.684	.600	6	14	102975-7
△		.584	.500	5	12	102975-6
△		.484	.400	4	10	102975-5
△		.384	.300	3	8	102975-4
△		.284	.200	2	6	102975-3
△		.184	.100	1	4	102975-2
△		.084	---	---	2	102975-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DATE	REVISED	BY	CHK	APP
00	00			

TE Connectivity  
 HEADER ASSY, MOD B, BREAKAWAY, DOUBLE ROW, 100X100 CL, RIGHT ANGLE WITH .025 SQ POSTS

SIZE: A1 | DATE: 100779 | DRAWING NO: G=102975 | REVISED PER: EDD-11-04820