



RECOMMENDED PC BOARD MOUNTING DIMENSIONS FOR .063 [1.60] THICK PC BOARD AND .012 [.305] STENCIL THICK.

- △ THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING.
- △ BREAKAWAY NOTCH ANGLE CAN BE ORIENTED TO THE RIGHT (AS SHOWN) OR TO THE LEFT
- △ GLASS FILLED THERMOPLASTIC (THAT WILL WITHSTAND IR REFLOW PROCESSING)
COLOR: BLACK.
- △ 0.000762 [.000030] GOLD ON CONTACT AREA,
0.00254-0.00508 [.000100-.000200] MATTE TIN-LEAD ALL OVER 0.00127 [.000050] NICKEL.
- △ PARTS PACKAGED IN TUBES.
- △ 0.000762 [.000030] GOLD ON CONTACT AREA,
0.00254-0.00508 [.000100-.000200] MATTE TIN
ALL OVER 0.00127 [.000050] NICKEL.
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

PLATING	C	B	A	NO. OF POSITIONS	PART NUMBER	PLATING	C	B	A	NO. OF POSITIONS	PART NUMBER	
OBsolete	△	△	△	39	80	9-146308-0	△	△	△	29	60	4-146308-1
OBsolete	△	△	△	38	78	8-146308-0	△	△	△	29	60	4-146308-0
OBsolete	△	△	△	37	76	8-146308-8	△	△	△	29	60	3-146308-0
OBsolete	△	△	△	36	74	8-146308-7	△	△	△	29	60	3-146308-7
OBsolete	△	△	△	35	72	8-146308-6	△	△	△	29	60	3-146308-6
OBsolete	△	△	△	34	70	8-146308-5	△	△	△	29	60	3-146308-5
OBsolete	△	△	△	33	68	8-146308-4	△	△	△	29	60	3-146308-4
OBsolete	△	△	△	32	66	8-146308-3	△	△	△	29	60	3-146308-3
OBsolete	△	△	△	31	64	8-146308-2	△	△	△	29	60	3-146308-2
OBsolete	△	△	△	30	62	8-146308-1	△	△	△	29	60	3-146308-1
OBsolete	△	△	△	29	60	8-146308-0	△	△	△	29	60	3-146308-0
OBsolete	△	△	△	28	58	7-146308-0	△	△	△	28	58	2-146308-0
OBsolete	△	△	△	27	56	7-146308-8	△	△	△	27	56	2-146308-8
OBsolete	△	△	△	26	54	7-146308-7	△	△	△	26	54	2-146308-7
OBsolete	△	△	△	25	52	7-146308-6	△	△	△	25	52	2-146308-6
OBsolete	△	△	△	24	50	7-146308-5	△	△	△	24	50	2-146308-5
OBsolete	△	△	△	23	48	7-146308-4	△	△	△	23	48	2-146308-4
OBsolete	△	△	△	22	46	7-146308-3	△	△	△	22	46	2-146308-3
OBsolete	△	△	△	21	44	7-146308-2	△	△	△	21	44	2-146308-2
OBsolete	△	△	△	20	42	7-146308-1	△	△	△	20	42	2-146308-1
OBsolete	△	△	△	19	40	7-146308-0	△	△	△	19	40	2-146308-0
OBsolete	△	△	△	18	38	6-146308-9	△	△	△	18	38	1-146308-9
OBsolete	△	△	△	17	36	6-146308-8	△	△	△	17	36	1-146308-8
OBsolete	△	△	△	16	34	6-146308-7	△	△	△	16	34	1-146308-7
OBsolete	△	△	△	15	32	6-146308-6	△	△	△	15	32	1-146308-6
OBsolete	△	△	△	14	30	6-146308-5	△	△	△	14	30	1-146308-5
OBsolete	△	△	△	13	28	6-146308-4	△	△	△	13	28	1-146308-4
OBsolete	△	△	△	12	26	6-146308-3	△	△	△	12	26	1-146308-3
OBsolete	△	△	△	11	24	6-146308-2	△	△	△	11	24	1-146308-2
OBsolete	△	△	△	10	22	6-146308-1	△	△	△	10	22	1-146308-1
OBsolete	△	△	△	9	20	6-146308-0	△	△	△	9	20	1-146308-0
OBsolete	△	△	△	8	18	6-146308-9	△	△	△	8	18	1-146308-9
OBsolete	△	△	△	7	16	6-146308-8	△	△	△	7	16	1-146308-8
OBsolete	△	△	△	6	14	5-146308-7	△	△	△	6	14	1-146308-7
OBsolete	△	△	△	5	12	5-146308-6	△	△	△	5	12	1-146308-6
OBsolete	△	△	△	4	10	5-146308-5	△	△	△	4	10	1-146308-5
OBsolete	△	△	△	3	8	5-146308-4	△	△	△	3	8	1-146308-4
OBsolete	△	△	△	2	6	5-146308-3	△	△	△	2	6	1-146308-3
OBsolete	△	△	△	1	4	5-146308-2	△	△	△	1	4	1-146308-2
OBsolete	△	△	△	0	2	5-146308-1	△	△	△	0	2	1-146308-1

THIS DRAWING IS A CONTROLLED DOCUMENT. **TE Connectivity**

DATE: 10/07/79
 PART: 146308
 REV: 1

TE Connectivity
 HEADERS ASSEMBLY, MOD B, BREAKAWAY,
 RIGHT ANGLE, DOUBLE ROW, HIGH TEMPERATURE,
 100 X 100 2/L, W/020 SQUARE POSTS

DATE: 10/07/79
 PART: 146308
 REV: 1