






PRODUCT NO  
SEE TABLE



REF  
 $\varnothing$  .006/0.15




SECTION A-A



w/WINDOW OPTION  
SEE TABLE

.004/0.10

STYLE D HOUSING  
SEE TABLE



DRAWN WITHOUT WINDOW OPTION

rev	ecn no	dr	date
AB	M06-0269	MNR	07/17/06
AC	M06-0356	MNR	09/08/06
AD	M08-0108	MHT	04/17/18
AE	M08-0230	MHT	08/14/08
AF	M08-0291	MHT	10/08/08
AG	N10-0078	Devid	3/23/10
AH	N10-0327	AZH	09/23/10

www.fciconnect.com		surface ISO 1302	tolerance std ISO 406 ISO 1101	projection ISO 1101	INCH/MM
Dr	E.KROPWIENICK	08/21/96	ANGULAR	size	A3
Eng	L.FYE	08/21/96	LINEAR	ECN	N10-0327
Chr	T.BREWBAKER	08/21/96	Product family	Spec ref	
Appr	T.BREWBAKER	08/21/96			
QUICKIE II HDR, D/R SLIMLINE SMT ASSEMBLY				72454	Rev. AH
catalog no				CUSTOMER	sheet 1 of 4

PDM: Rev:AH

STATUS Released

Printed: Apr 12, 2011




Copyright FCI

REV F - 000-00



PRODUCT NO SEE TABLE	PLATING CODE	CONTACT AREA PLATING	SOLDER TAIL PLATING
	AA	30u"/.76u AU OVER 50u"/1.27u NI	100u"/2.54u TIN OVER 50u"/1.27u NI
	4	100u"/3.05u Sn OVER 50u"/1.27u NI	100u"/3.05u Sn OVER 50u"/1.27u NI

LEAD FREE PLATING	AA	30u"/.76u AU OVER 50u"/1.27u NI	100u"/2.54u TIN OVER 50u"/1.27u NI
	4	100u"/3.05u Sn OVER 50u"/1.27u NI	100u"/3.05u Sn OVER 50u"/1.27u NI

NOTE 11



RECOMMENDED PAD LAYOUT  
SCALE 4/1



NOTES:

- BODY MATERIAL: PCT, GLASS FIBER REINFORCED, FLAME RETARDANT PER UL-94V-0.  
COLOR: BLACK  
OR  
MINERAL FILLED LCP, FLAME RETARDANT PER UL-94V-0  
COLOR: BLACK
- PIN MATERIAL: PHOS-BRONZE.
- PINS DELETED FROM SPECIFIED LOCATIONS FOR POLARIZATION. SEE TABLE FOR LOCATIONS.
- PACKAGING OPTIONS: CHECK SPECIFIC PART NUMBERS FOR AVAILABILITY. PART NUMBERS WITHOUT A SUFFIX ARE PACKAGED IN TRAYS. PART NUMBERS FOLLOWED BY A "V" SUFFIX ARE PACKAGED TAPE-ON-REEL WITH A PICK-UP CAP INSTALLED. VACUUM CAP TO BE CENTRALLY LOCATED REGARDLESS OF NUMBER OF POSITIONS. PART NUMBERS FOLLOWED BY A "B" SUFFIX ARE ASSEMBLED WITH VACUUM PICK-UP CAPS INSTALLED AND PACKAGED IN TRAYS
- MEASURED WITH PART IN RESTRAINED CONDITION.
- TWO SIDES OF PIN TIPS NOT PLATED. TYPICAL BOTH ENDS (SIMPLEX PLATING ONLY).
- 2 LBS/0.9KG MIN PIN RETENTION IN EITHER DIRECTION.
- ADD 'LF' SUFFIX AT THE END OF PART NUMBER FOR LEAD FREE OPTION.
- THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATION AS DESCRIBED IN GS-22-008.
- THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10-20 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN. SEE APPLICATION NOTES/PROCEDURES IF THEY ARE AVAILABLE.
- \*THIS PRODUCT HAS 100% TIN PLATING IN THE INTERFACE AND HAS NOT BEEN TESTED FOR WHISKER GROWTH IN ALL INTERCONNECT ENVIRONMENTS.\*

www.fciconnect.com			surface ISO 1302	tolerance std ISO 406 ISO 1101	projection INCH/MM	INCH/MM
			TOLERANCES UNLESS OTHERWISE SPECIFIED			
Dr	E.KROPWIENICK	08/21/96	ANGULAR	XXX.01/XX0.3	size	Scale
Eng	L.FYE	08/21/96	LINEAR	XXX0.005/XXX0.13	A3	21
Chr	T.BREWBAKER	08/21/96	0' ±*	XXX0.002/XXX0.051	ECN	N10-0327
Appr	T.BREWBAKER	08/21/96	Product family		Spec ref	
FCI			QUICKIE II HDR, D/R SLIMLINE SMT ASSEMBLY		72454	Rev. AH
catalog no			CUSTOMER		sheet 2 of 4	

PDM: Rev:AH

STATUS Released


Printed: Apr 12, 2011

REV F - 2004-07


1

2

PRODUCT NO  
SEE TABLE



UN-REELING DIRECTION OF FEED →



www.fciconnect.com			surface ISO 1302	tolerance std ISO 406 ISO 1101	projection ASME Y14.5 ISO 1101	INCH/MM
			TOLERANCES UNLESS OTHERWISE SPECIFIED			
Dr	E.KROPWIENICK	08/21/96	ANGULAR	XXX.01/XX0.3	size	Scale
Eng	L.FYE	08/21/96	LINEAR	.XXXX.005/XX40.13	A3	2:1
Chr	T.BREWBAKER	08/21/96	Ø ±*	.XXXXX.002/XXXX0.051	ECN	N10-0327
Appr	T.BREWBAKER	08/21/96	Product family		Spec ref	
			QUICKIE II HDR, D/R SLIMLINE SMT ASSEMBLY		72454	Rev. AH
catalog no			CUSTOMER		sheet 3 of 4	

PDM: Rev:AH

STATUS Released

Printed: Apr 12, 2011

REV F - 2004-07

1		2			3			4				
PRODUCT NUMBER	NO. OF POSITIONS	DIM B	DIM C	STYLE	POLARIZED POSITION	WINDOW OPTION	PLATING CODE	PACKAGING	TAPE WIDTH DIM M	POCKET DEPTH	DIM N	LEAD FREE OPTION
72454-008	2 X 4	.610/15.50	.690/15.33	A	-	N	AA	TRAY	--	--	--	NOTE 8,9
72454-010	2 X 5	.710/18.03	.790/20.07	A	-	N	AA	TRAY	--	--	--	
72454-010V	2 X 5	.710/18.03	.790/20.07	A	-	N	AA	TAPE DN REEL	1.260/32.00	.515/13.08	.790/20.07	
72454-014	2 X 7	.910/23.11	.99/25.2	C	-	N	AA	TRAY	--	--	--	
72454-014V	2 X 7	.910/23.11	.99/25.2	C	-	N	AA	TAPE DN REEL	1.732/44.00	.515/13.08	1.090/27.69	
72454-016	2 X 8	1.010/25.65	1.090/27.69	D	-	N	AA	TRAY	--	--	--	
72454-016V	2 X 8	1.010/25.65	1.090/27.69	D	-	N	AA	TAPE DN REEL	1.732/44.00	.515/13.08	1.090/27.69	
72454-020	2 X 10	1.210/30.73	1.290/32.77	D	-	N	AA	TRAY	--	--	--	
72454-020V	2 X 10	1.210/30.73	1.290/32.77	D	-	N	AA	TAPE-DN-REEL	2.205/56.00	.505/12.83	1.290/32.77	
72454-021	2 X 11	1.310/33.27	1.390/35.31	D	12	N	AA	TRAY	--	--	--	
72454-022	2 X 11	1.310/33.27	1.390/35.31	D	-	N	AA	TRAY	--	--	--	
72454-024	2 X 12	1.410/35.81	1.490/37.9	D	-	N	AA	--	--	--	--	
72454-024V	2 X 12	1.410/35.81	1.490/37.9	D	-	N	AA	TAPE-DN-REEL	2.205/56.00	.515/13.08	1.490/37.85	
72454-026	2 X 13	1.510/38.35	1.590/40.39	D	-	N	AA	TRAY	--	--	--	
72454-030	2 X 15	1.710/43.43	1.790/45.47	D	-	N	AA	TRAY	--	--	--	
72454-030V	2 X 15	1.710/43.43	1.790/45.47	D	-	N	AA	TAPE-DN-REEL	2.834/72.00	0.787/20.00	1.771/45.00	
72454-034	2 X 17	1.910/48.51	1.990/50.60	D	-	N	AA	TRAY	--	--	--	
72454-040	2 X 20	2.210/56.13	2.290/58.17	D	-	N	4	TRAY	--	--	--	
72454-040V	2 X 20	2.210/56.13	2.290/58.17	D	-	N	4	TAPE-DN-REEL	3.465/88.00	0.787/20.00	2.290/58.25	
72454-041	2 X 20	2.210/56.13	2.290/58.17	D	-	N	AA	TRAY	--	--	--	
72454-044	2 X 22	2.410/61.21	2.490/63.25	D	-	N	AA	TRAY	--	--	--	
72454-050	2 X 25	2.710/68.83	2.790/70.87	D	-	N	AA	TRAY	--	--	--	
72454-051	2 X 10	1.210/30.73	1.290/32.77	D	-	Y	AA	TRAY	--	--	--	
72454-051V	2 X 10	1.210/30.73	1.290/32.77	D	-	Y	AA	TAPE-DN-REEL	2.205/56.00	.505/12.83	1.290/32.77	
72454-052	2 X 20	2.210/56.13	2.290/58.17	D	20	N	AA	TRAY	--	--	--	
72454-053V	2 X 5	0.710/18.03	0.790/20.07	A	9	N	AA	TAPE DN REEL	1.260/32.00	.515/13.08	.790/20.07	

www.fciconnect.com		surface ISO 1302	tolerance std ISO 406 ISO 1101	projection INCH/MM
		TOLERANCES UNLESS OTHERWISE SPECIFIED		
Dr	E.KROPWIENICK	08/21/96	ANGULAR	size A3
Eng	L.FYE	08/21/96	LINEAR	
Chr	T.BREWBAKER	08/21/96	0° ±*	Scale 3:1
Appr	T.BREWBAKER	08/21/96	Product family	ECN N10-0327
FCI		QUICKIE II HDR. D/R SLIMLINE SMT ASSEMBLY		Spec ref
catalog no		72454		Rev. AH

PDM: Rev:AH STATUS Released Printed: Apr 12, 2011

REV F - 2004-07

1

2

CUSTOMER sheet 4 of 4