



NO. OF CCTS	DIMN. 'A'	DIMN. 'B'
2	(5.08) .200	(2.54) .100
3	(7.62) .300	(5.08) .200
4	(10.16) .400	(7.62) .300
5	(12.70) .500	(10.16) .400
6	(15.24) .600	(12.70) .500
7	(17.78) .700	(15.24) .600
8	(20.32) .800	(17.78) .700
9	(22.86) .900	(20.32) .800
10	(25.40) 1.000	(22.86) .900
11	(27.94) 1.100	(25.40) 1.000
12	(30.48) 1.200	(27.94) 1.100
13	(33.02) 1.300	(30.48) 1.200
14	(35.56) 1.400	(33.02) 1.300
15	(38.10) 1.500	(35.56) 1.400
16	(40.64) 1.600	(38.10) 1.500
17	(43.18) 1.700	(40.64) 1.600
18	(45.72) 1.800	(43.18) 1.700
19	(48.26) 1.900	(45.72) 1.800
20	(50.80) 2.000	(48.26) 1.900
21	(53.34) 2.100	(50.80) 2.000
22	(55.88) 2.200	(53.34) 2.100
23	(58.42) 2.300	(55.88) 2.200
24	(60.96) 2.400	(58.42) 2.300
25	(63.50) 2.500	(60.96) 2.400
26	(66.04) 2.600	(63.50) 2.500
27	(68.58) 2.700	(66.04) 2.600
28	(71.12) 2.800	(68.58) 2.700




AE-6410- N * (*) - *

NO. OF CCTS



WAFER ASSY. OPTION

VOIDED CIRCUIT CODE NO. CORRESPONDS TO CIRCUIT NO. VOIDED. MULTIPLE VOIDS START WITH 51
BLANK = NONE

PLATING TYPE



- NOTES:
1. WAFER MATERIAL: NYLON. UL94V-0. PIN MATERIAL: BRASS
 2. FINISH:
102 = OVERALL TIN: 0.00508/0.00200 MIN. OVER 0.00254/0.00100 MIN. COPPER
154 = OVERALL TIN: 0.00254/0.0100 MIN. OVER 0.00127/0.00050 MIN. NICKEL
501 = OVERALL GOLD: 0.00051/0.00020 MIN. OVER 0.00076/0.00030 MIN. NICKEL
503 = OVERALL GOLD: 0.00076/0.00030 MIN. OVER 0.00127/0.00050 MIN. NICKEL
509 = OVERALL GOLD: 0.00127/0.00050 MIN. OVER 0.00076/0.00030 MIN. NICKEL
516 = OVERALL GOLD: 0.00025/0.00010 MIN. OVER 0.00076/0.00030 MIN. NICKEL
 3. THIS PART CONFORMS TO MOLEX PROD. SPEC. PS-99020-0088.
 4. PACKAGING: PER PK-6373-001
 5. PIN SOLDERABILITY PER MOLEX SPEC. SMES-152
 6. SINGLE RAMP ON 2-6 CCTS TWO RAMP ON 7-28 CCTS. AS SHOWN.
 7. PIN PUSH OUT FORCE: (0.907 Kg)/2lbs MIN.
 8. PCB THICKNESS 1.6MM
 9. WAFERS STACKABLE END TO END WITH (2.54)/.100 BETWEEN END PINS
 10. THIS PART CONFORMS TO CLASS B REQUIREMENTS OF COSMETIC SPECIFICATION PS-45499-002.
 11. CIRCUIT 1 DESIGNATION IS USED TO DEFINE VOID LOCATION. CIRCUIT 1 MAY OR MAY NOT LINE UP WITH CIRCUIT 1 ON THE MATING HOUSING.



ADD/REVISE NOTES	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
		mm	INCH	MM/IN	5:1	METRIC	⊕	
DEC. NO. UCP-2010-2318 2010/07/06	▽=0	4 PLACES ± --- ± ---		DRAWN BY T. MAHON	DATE 28/01/03	TITLE		
DRW/CHK/APP/CHK/SS/CHK/APP/ESM/TH 2010/07/07	▽=0	3 PLACES ± --- ± .010		CHECKED BY BMAGUIRE	DATE 28/01/03	WAFER, FRICTION LOCK KK (2.54)/.100 FOR (0.64)/.025 SQ. PINS		
REV		2 PLACES ± 0.25 ± .014		APPROVED BY JDENNEHY	DATE 2005/03/11	MOLEX INCORPORATED		
		1 PLACE ± 0.35 ± ---		MATERIAL NO.	DOCUMENT NO.			
		ANGULAR ± 5 °		SEE CHART	SDAE-6410-N			
				DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		SHEET NO. 1 OF 4

ENG. NO.	AE-6410-NA (501)	AE-6410-NA (516)	AE-6410-NK (516)	AE-6410-NC (501)	AE-6410-NA (509)	AE-6410-NS (501)	AE-6410-NA (503)							
DIMN. "D"	(7.50 ±0.25) 295 ±0.00	(7.50 ±0.25) 295 ±0.00	(9.22) .363 REF	(7.14 ±0.25) .281 ±0.00	(7.50 ±0.25) 295 ±0.00	(7.50 ±0.25) 295 ±0.00	(7.50 ±0.25) 295 ±0.00							
DIMN. "C"	(14.22) / .560	(14.22) / .560	(15.88) / .625	(20.32) / .800	(14.22) / .560	(16.51) / .649	(14.22) / .560							
DIMN. "F"	(3.56) / .140 REF	(3.56) / .140 REF	(3.48 ±0.25) .137 ±0.00	(10.00) / .394 REF	(3.56) / .140 REF	(5.84) / .230 REF	(3.56) / .140 REF							
PLATING	501	516	516	501	509	501	503							
2	AE-6410-24A509	22-29-2021	AE-6410-24A516	22-29-2022	AE-6410-24A509	38-00-0932	AE-6410-24A509	NOT TOOLED	AE-6410-24A509	38-00-7250	NOT TOOLED	AE-6410-24A509	38-00-7062	
3	3 A(501)	2031	3 A(516)	2032	3 K(516)	0933	3 C(501)	38-00-5909	3 A(509)	NOT TOOLED	3 A(503)	7063		
4	4 A(501)	2041	4 A(516)	2042	4 K(516)	0934	4 C(501)	NOT TOOLED	4 A(509)	38-00-7251	AE-6410-24A509	38-00-7666	4 A	7064
5	5 A(501)	2051	5 A(516)	2052	5 K(516)	0935	5 C(501)	↑	5 A(509)	NOT TOOLED	NOT TOOLED	5 A	7065	
6	6 A(501)	2061	6 A(516)	2062	6 K(516)	0936	6 C(501)	↑	6 A(509)	↑	6 S(501)	38-00-7667	6 A	7066
7	7 A(501)	2071	7 A(516)	2072	7 K(516)	0937	7 C(501)	↑	7 A(509)	↑	NOT TOOLED	7 A	7067	
8	8 A(501)	2081	8 A(516)	2082	8 K(516)	0938	8 C(501)	↑	8 A(509)	↑	↑	8 A	38-00-7068	
9	9 A(501)	2091	9 A(516)	2092	9 K(516)	0939	9 C(501)	↑	9 A(509)	↑	↑	9 A	NOT TOOLED	
10	10 A(501)	2101	10 A(516)	2102	10 K(516)	0940	10 C(501)	↑	10 A(509)	↑	↑	10 A	NOT TOOLED	
11	11 A(501)	2111	11 A(516)	2112	11 K(516)	0941	11 C(501)	↑	11 A(509)	↑	↑	11 A	NOT TOOLED	
12	12 A(501)	2121	12 A(516)	2122	12 K(516)	0942	12 C(501)	↑	12 A(509)	↑	↑	12 A	38-00-7072	
13	13 A(501)	2131	13 A(516)	2132	13 K(516)	0943	13 C(501)	↑	13 A(509)	↑	↑	13 A	NOT TOOLED	
14	14 A(501)	2141	14 A(516)	2142	14 K(516)	0944	14 C(501)	↑	14 A(509)	↑	↑	14 A	38-00-7074	
15	15 A(501)	2151	15 A(516)	2152	15 K(516)	0945	15 C(501)	↑	15 A(509)	↑	↑	15 A	NOT TOOLED	
16	16 A(501)	2161	16 A(516)	2162	16 K(516)	0946	16 C(501)	↑	16 A(509)	↑	↑	16 A	↑	
17	17 A(501)	2171	17 A(516)	2172	17 K(516)	0947	17 C(501)	↑	17 A(509)	↑	↑	17 A	↑	
18	18 A(501)	2181	18 A(516)	2182	18 K(516)	0948	18 C(501)	↑	18 A(509)	↑	↑	18 A	↑	
19	19 A(501)	2191	19 A(516)	2192	19 K(516)	0949	19 C(501)	↑	19 A(509)	↑	↑	19 A	NOT TOOLED	
20	20 A(501)	2201	20 A(516)	2202	20 K(516)	0950	20 C(501)	↑	20 A(509)	↑	↑	20 A	38-00-7080	
21	21 A(501)	2211	21 A(516)	2212	21 K(516)	0951	21 C(501)	↑	21 A(509)	↑	↑	21 A	NOT TOOLED	
22	22 A(501)	2221	22 A(516)	2222	22 K(516)	0952	22 C(501)	↑	22 A(509)	↑	↑	22 A	NOT TOOLED	
23	23 A(501)	2231	23 A(516)	2232	23 K(516)	0953	23 C(501)	↑	23 A(509)	↑	↑	23 A	NOT TOOLED	
24	24 A(501)	2241	24 A(516)	2242	24 K(516)	0954	24 C(501)	↑	24 A(509)	↑	↑	24 A	38-00-0441	
25	25 A(501)	2251	25 A(516)	2252	25 K(516)	0955	25 C(501)	↑	25 A(509)	↑	↑	25 A	NOT TOOLED	
26	26 A(501)	2261	26 A(516)	2262	26 K(516)	0956	26 C(501)	↑	26 A(509)	↑	↑	26 A	↑	
27	27 A(501)	2271	27 A(516)	2272	27 K(516)	0957	27 C(501)	↑	27 A(509)	↑	↑	27 A(503)	↑	
28	AE-6410-24A509	22-29-2281	AE-6410-24A516	22-29-2282	AE-6410-24A516	38-00-0958	AE-6410-24A509	NOT TOOLED	AE-6410-24A509	NOT TOOLED	NOT TOOLED	AE-6410-24A509	NOT TOOLED	

REMOVE PLATING DIM LEC NO: UCP 2010-2318 2010/07/06 DRAWN: KIPPER 2010/07/07 CHKD: SMOUSEK 2010/07/07 APPR: SMITH 2010/07/07	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	
				MM/IN		4:1	METRIC		
		4 PLACES ± --- ± ---		DRAWN BY T. MAHON		DATE 28/01/03		TITLE	
		3 PLACES ± --- ± .010		CHECKED BY BMAGUIRE		DATE 28/01/03		WAFER, FRICTION LOCK KK (2.54)/.100 FOR (0.64)/.025 SQ. PINS	
2 PLACES ± 0.25 ± .014		APPROVED BY JDENNEHY		DATE 2005/03/11		MOLEX INCORPORATED			
1 PLACE ± 0.35 ± ---		ANGULAR ± .5 °		MATERIAL NO.		DOCUMENT NO.			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART		SDAE-6410-N		SHEET NO. 3 OF 4			
		SIZE A		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					

10 9 8 7 6 5 4 3 2 1

VOIDED CIRCUIT OPTION

PART No.	ENG No.	CKT SIZE	VOID LOCATION	DIM D	DIM F (REF)	PLATING
38-00-7222	AE-6410-3A(102)-2	3	2	(7.50)/.295	(3.56)/.140	102
38-00-4749	-4A(102)-3	4	3	(7.50)/.295	(3.56)/.140	102
38-00-0611	-5A(102)-3	5	3	(7.50)/.295	(3.56)/.140	102
38-00-0089	-6A(102)-3	6	3	(7.50)/.295	(3.56)/.140	102
38-00-0090	-6A(102)-51	6	3,4,5	(7.50)/.295	(3.56)/.140	102
38-00-5370	-15A(102)-02	15	2	(7.50)/.295	(3.56)/.140	102
38-00-5371	-19A(102)-12	19	12	(7.50)/.295	(3.56)/.140	102
38-00-7688	-12A(102)-09	12	9	(7.50)/.295	(3.56)/.140	102

CORRECT ENG. NO. DEC NO: UCP2010-2318 DRW:MM/PPR 2010/07/06 CHK:SSOUSEK 2010/07/07 APPR:F.SMITH 2010/07/07 REV BB1	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED) <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> <tr> <td>4 PLACES</td> <td>± .010</td> <td>± .0004</td> </tr> <tr> <td>3 PLACES</td> <td>± .012</td> <td>± .0005</td> </tr> <tr> <td>2 PLACES</td> <td>± .015</td> <td>± .0006</td> </tr> <tr> <td>1 PLACE</td> <td>± .020</td> <td>± .0008</td> </tr> <tr> <td colspan="3" style="text-align: center;">ANGULAR ± .5 °</td> </tr> </table>		mm	INCH	4 PLACES	± .010	± .0004	3 PLACES	± .012	± .0005	2 PLACES	± .015	± .0006	1 PLACE	± .020	± .0008	ANGULAR ± .5 °			DIMENSION STYLE MM/IN DRAWN BY: T. MAHON DATE: 28/01/03 CHECKED BY: BMAGUIRE DATE: 28/01/03 APPROVED BY: JDENNEHY DATE: 2005/03/11	SCALE 4:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	TITLE WAFER, FRICTION LOCK KK (2.54)/.100 FOR (0.64)/.025 SQ. PINS MOLEX INCORPORATED SDAE-6410-N
		mm	INCH																						
	4 PLACES	± .010	± .0004																						
	3 PLACES	± .012	± .0005																						
2 PLACES	± .015	± .0006																							
1 PLACE	± .020	± .0008																							
ANGULAR ± .5 °																									
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO. SEE TABLE		DOCUMENT NO. SDAE-6410-N		SHEET NO. 4 OF 4																			
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																									
SIZE A3																									

9 8 7 6 5 4 3 2 1