



REV.	DESCRIPTION	DATE	DESIGNED
△	Color part No. is added.	AUG. 3.2007	T.S
△	Circuit No. are added.	JAN.23.2008	T.S

- NOTE**
- 1.Connector part:See the DWG. of ZE Connector.
 - 2.Quantity to be packaged:800pcs/reel
 - 3.Leading tape length.



- 4.Cover tape peel strength:0.1~1N (Peel speed:300mm/minute)



- 5.Material:Carrier tape: Polyester(PET)
Cover tape : Polyester(PET)
Reel :Flange: Polystyrene(PS)
Core: Polypropylene(PP)
Polystyrene(PS)

- 6.Unless otherwise specified, tolerances are ±0.3

Cir- size	Dimensions							
	A	B	C	D	E	F	G	
7	15.4	9.7	32.0	14.2	28.4	33.5	14.8	
8	16.9	11.2	32.0	14.2	28.4	33.5	16.3	
9	18.4	12.7	32.0	14.2	28.4	33.5	17.8	
10	19.9	14.2	32.0	14.2	28.4	33.5	19.3	
11	21.4	15.7	44.0	20.2	40.4	45.5	20.8	
12	22.9	17.2	44.0	20.2	40.4	45.5	22.3	
13	24.4	18.7	44.0	20.2	40.4	45.5	23.8	
△	14	25.9	20.2	44.0	20.2	40.4	45.5	25.3
△	15	27.4	21.7	44.0	20.2	40.4	45.5	26.8
△	16	28.9	23.2	44.0	20.2	40.4	45.5	28.3

Color	Part No.
Natural	BM()-ZESS-TBT (LF) (SN)
△ Moss green	BM()-ZEMGS-TBT (LF) (SN)

No.	PART NAME	MATERIAL	SURFACE FINISH	REMARKS
A2	METRIC 3:1	PROJECTION DATE AUG. 3.2007	OUTDOOR	
APPROVED	CHECKED	DESIGNED	DRAWN	SERIES NAME
S.K	E.N	T.S		ZE CONNECTOR EMBOSSED-TAPING
				PART No. BM()S-TBT (LF) (SN)
				DRAWING No. KR D-4178B

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J.S.T. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

EC4113-2