THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
© COPYRIGHT — By — ALL RIGHTS RESERVED

UOC	DIST
CM	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	J2	REVISED PER ECO-11-004835	11MAR11	RK	HMR











RECOMMENDED MOUNTING HOLE PATTERN FOR 1.57[.062] THICK P.C. BOARD



VIEW A–A
SCALE 10:1

1. MATERIAL
HOUSING: THERMOPLASTIC POLYESTER,GLASS FILLED,UL94V-0.
POST: COPPER ALLOY
2. FINISH
HOUSING: NATURAL
POST: BRIGHT TIN-LEAD (93/7) PLATE, 0.0038[.000150]-0.0088[.000350] THICK OVER NICKEL UNDERPLATE, 0.0013[.000050] MIN THICK.
4. POST SOLDERTAILS COMPLY WITH AMP SOLDERABILITY SPEC 109-11-2.
5. POST WITHSTANDS 13.34N (3 LB) MIN AXIAL FORCE IN EITHER DIRECTION WITHOUT DISLODGING.
6. APPLIES AT -A- .
7. APPLIES WHEN THE HEADER IS STRAIGHT.
8. PLASTIC PROJECTIONS PERMITTED IN THIS ZONE.
9. COORDINATE DIMENSIONS APPLIES FROM THE CENTER OF THE ACTUAL FEATURE.
10. SOLDER SIDE OF BOARD IS SHOWN.
11. THE RENTENTION TABS PROVIDE A ONE-TIME INTERFERENCE FIT IN THE 1.63[.064] DIAMETER BOARD HOLE FOR HEADER ASSEMBLY RETENTION DURING SOLDERING. FOUR TABS PER PEG, TWO PEGS PER HEADER ASSEMBLY (ONE PEG ONLY FOR 2 POSITION SIZE).
12. UL MARKING MAY NOT APPEAR ON THE 2 OR 3 POSITION SIZES. CSA MARKING MAY NOT APPEAR ON THE 2 POSITION SIZE.
13. DIMENSIONS IN BRACKETS ARE IN INCHES.
14. ALL POSITION SIZES HAVE THE BACKWALL NOTCHED ON BOTH ENDS AS SHOWN. THE 2 THRU 5 POSITION SIZES HAVE SOLID BACKWALLS. POSITION SIZES 6 AND ABOVE HAVE AN INTERRUPTED BACKWALL AT VARIOUS LOCATIONS (SEE TABLE FOR INTERRUPTION(S) LOCATIONS).
15. EDGE OF POLARIZING LOCK WALL TO BE IN LINE WITH CENTERLINE OF ADJACENT POST WITHIN ±0.13 [.005].
16. NOTCH SHOWN MAY OR MAY NOT APPEAR.
17. FINISH
HOUSING: NATURAL
POST: MATTE TIN PLATE, .000150" MIN THICK OVER NICKEL.
18. OBSOLETE PART NUMBER

NOTES	FINISH	BACKWALL INTERUPTION(S) BETWEEN POST	L	NO. OF CIRCUITS	PART NUMBER
17		4&5, 7&8, 11&12, 14&15	71.20 [2.803]	18	4-644615-8
		4&5, 7&8, 10&11, 13&14	67.23 [2.647]	17	4-644615-7
		4&5, 8&9, 12&13	63.27 [2.491]	16	4-644615-6
		4&5, 8&9, 11&12	59.31 [2.335]	15	4-644615-5
		4&5 7&8, 10&11	55.35 [2.179]	14	4-644615-4
		4&5 7&8, 10&11	51.38 [2.023]	13	4-644615-3
		4&5, 8&9	47.42 [1.867]	12	4-644615-2
		4&5, 7&8	43.46 [1.711]	11	4-644615-1
		3&4, 7&8	39.50 [1.555]	10	4-644615-0
		3&4, 6&7	35.53 [1.399]	9	3-644615-9
		4&5	31.57 [1.243]	8	3-644615-8
		4&5	27.61 [1.087]	7	3-644615-7
		3&4	23.65 [.931]	6	3-644615-6
		NONE	19.69 [.775]	5	3-644615-5
		NONE	15.72 [.619]	4	3-644615-4
		NONE	11.76 [.463]	3	3-644615-3
		NONE	7.80 [.307]	2	3-644615-2
18	2	4&5, 7&8, 11&12, 14&15	71.20 [2.803]	18	1-644615-8
18		4&5, 7&8, 10&11, 13&14	67.23 [2.647]	17	1-644615-7
18		4&5, 8&9, 12&13	63.27 [2.491]	16	1-644615-6
18		4&5, 8&9, 11&12	59.31 [2.335]	15	1-644615-5
18		4&5 7&8, 10&11	55.35 [2.179]	14	1-644615-4
18		4&5 7&8, 10&11	51.38 [2.023]	13	1-644615-3
18		4&5, 8&9	47.42 [1.867]	12	1-644615-2
18		4&5, 7&8	43.46 [1.711]	11	1-644615-1
18		3&4, 7&8	39.50 [1.555]	10	1-644615-0
18		3&4, 6&7	35.53 [1.399]	9	644615-9
18		4&5	31.57 [1.243]	8	644615-8
18		4&5	27.61 [1.087]	7	644615-7
18		3&4	23.65 [.931]	6	644615-6
18		NONE	19.69 [.775]	5	644615-5
18		NONE	15.72 [.619]	4	644615-4
18		NONE	11.76 [.463]	3	644615-3
18	2	NONE	7.80 [.307]	2	644615-2

THIS DRAWING IS A CONTROLLED DOCUMENT.

	NAME	DATE
DRN	S. CARPENTER	13AUG2003
CHK	D. BOSSI	13AUG2003
APVD	D. BOSSI	13AUG2003

DIMENSIONS: mm [INCHES]
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± –, 1 PLC ± –, 2 PLC ± –, 3 PLC ± –, 4 PLC ± –, ANGLES ± –
PRODUCT SPEC: —
APPLICATION SPEC: —
WEIGHT: —
MATERIAL: 1
FINISH: 2 17

TE Connectivity

NAME: MTA-156 HEADER ASSEMBLY, POLARIZED LOCK, STRAIGHT .045 SQUARE POST, TIN OR TIN-LEAD PLATED W/RETENTION PEGS

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1		C-644615	—

CUSTOMER DRAWING | SCALE 5:1 | SHEET 1 OF 1 | REV J2

4605 (3/11)

Downloaded from Elcodis.com electronic components distributor