

THIS DRAWING IS UNPUBLISHED
 ALL RIGHTS RESERVED

REV	DATE	DESCRIPTION	BY	APP
00		SEE SHEET 1		

- △ COORDINATE DIMENSION APPLIES FROM BASIC LOCATION.
- △ 10 AND 14 POSITION SIZES CONTAIN ONLY ONE SLOT FOR SNAP-IN POLARIZER (MILITARY POLARIZATION) LOCATED AS SHOWN.
- △ 10 POSITION SIZES CONTAIN ONLY ONE SLOT FOR DUAL POLARIZATION, LOCATED AS SHOWN.
- 4. RECOMMENDED PRINTED CIRCUIT BOARD THICKNESS IS 1.57 [0.62].
- △ POSTS:
 GOLD FLASH OVER PALLADIUM-NICKEL PLATE, 0.38µm [0.00015] MIN TOTAL ON THE LOCALIZED PLATE AREA,
 2.54µm [0.00100] MIN TIN-LEAD PLATE ON THE SOLDER-TAIL,
 1.27µm [0.00050] MIN NICKEL UNDERPLATE ON THE ENTIRE POST,
 OR
 0.38µm [0.00015] MIN GOLD PLATE ON THE LOCALIZED PLATE AREA,
 2.54µm [0.00100] MIN TIN-LEAD PLATE ON THE SOLDER-TAIL,
 1.27µm [0.00050] MIN NICKEL UNDERPLATE ON THE ENTIRE POST.
- △ MATERIAL:
 HOUSING: GLASS FILLED NYLON OR POLYESTER, 94V-0 RATED, BLACK.
 POSTS: BRASS.

OBSOLETE	53.34	65.02	65.02	75.18	71.12	60.96	44	1-102159-3
	2.100	2.560	2.560	2.960	2.800	2.400		
	78.74	90.42	90.42	100.58	96.52	86.36	64	1-102159-2
	3.100	3.560	3.560	3.960	3.800	3.400		
	73.66	85.34	85.34	95.50	91.44	81.28	60	1-102159-1
	2.900	3.360	3.360	3.760	3.600	3.200		
	60.96	72.64	72.64	82.80	78.74	68.58	50	1-102159-0
	2.400	2.860	2.860	3.260	3.100	2.700		
	48.26	59.94	59.94	70.10	66.04	55.88	40	102159-9
	1.900	2.360	2.360	2.760	2.600	2.200		
	40.64	52.32	52.32	62.48	58.42	48.26	34	102159-8
	1.600	2.060	2.060	2.460	2.300	1.900		
	35.56	47.24	47.24	57.40	53.34	43.18	30	102159-7
	1.400	1.860	1.860	2.260	2.100	1.700		
	30.48	42.16	42.16	52.32	48.26	38.10	26	102159-6
	1.200	1.660	1.660	2.060	1.900	1.500		
	27.94	39.62	39.62	49.78	45.72	35.56		
OBSOLETE	1.100	1.560	1.560	1.960	1.800	1.400	24	102159-5
	22.86	34.54	34.54	44.70	40.64	30.48	20	102159-4
	1.900	1.360	1.360	1.760	1.600	1.200		
	17.78	29.46	29.46	39.62	35.56	25.40	16	102159-3
	1.700	1.160	1.160	1.560	1.400	1.000		
	15.24	26.92	26.92	37.08	33.02	22.86	14	102159-2
	1.600	1.060	1.060	1.460	1.300	1.900		
	10.16	21.84	21.84	32.00	27.94	17.78	10	102159-1
	1.400	1.860	1.860	1.260	1.100	1.700		
F	E	D	C	B	A	NO OF POSN	PART NUMBER	

THIS DRAWING IS A CONTROLLED DOCUMENT.		REV. NO.	0-31-81
DRAWING NO.		REV. DATE	11/28/81
DRAWING TITLE		REV. DESCRIPTION	
DRAWING SCALE		REV. DATE	
DRAWING UNIT		REV. DESCRIPTION	
DRAWING SHEET		REV. DATE	
DRAWING PART		REV. DESCRIPTION	
DRAWING PROJECT		REV. DATE	
DRAWING CUSTOMER DRAWING		REV. DESCRIPTION	

TE Connectivity
 HEADERS ASSY, UNIVERSAL AMP-LATCH
 108-40018
 DATE: 11/28/81
 DRAWING NO: 100779
 REV: 0
 SHEET: 4.1 OF 2